

**PART 9
INDEX**

A

acceleration.....	2-11, 2-25, 4-46
<i>see also</i> performance, train	
accessibility	
as quality of service factor.....	3-11, 3-37
doorways.....	7-31
persons with disabilities.....	2-6, 7-16, 7-26
achievable capacity.....	5-1, 5-2, 5-3, 5-4, 5-5, 5-31, 5-34, 5-36, 5-49, 5-58, 5-79, 5-93
ADA	
<i>see</i> Americans with Disabilities Act	
Adelaide, Australia	
guided busway.....	2-8
aerial cableway	
<i>see</i> tramway, aerial <i>and</i> ropeways	
AGT	
<i>see</i> automated guideway transit	
air conditioning.....	3-21, 3-22
air quality.....	2-1
Alaska Marine Highway System.....	2-37
Albuquerque, NM	
bus.....	2-12, 4-7
bus stop.....	2-41
station amenities.....	7-46
amenities	
air conditioning.....	3-22
art.....	7-45
as quality of service factor.....	3-21, 7-45
benches.....	3-21, 7-3, 7-45
bicycle lockers.....	3-13, 7-47
bicycle racks.....	3-11, 3-12, 3-13, 4-6, 7-47
heating.....	3-22
impact on waiting area size.....	7-46
information displays.....	3-22
landscaping.....	7-45
lighting.....	3-10, 3-22, 7-45
placement.....	7-46
shelters.....	3-21, 7-3, 7-28, 7-45, 7-46
telephones.....	3-22, 7-45
ticket machines.....	7-4
trash receptacles.....	3-22, 7-45
vending facilities.....	3-22, 7-45
Americans with Disabilities Act	
comfort and convenience.....	3-9
demand-responsive transportation ...	2-6, 4-61
elevators.....	7-38
low-floor vehicles.....	5-38
passenger information.....	5-78, 7-17
station platforms.....	5-38, 7-16, 7-17
transit information.....	5-14
wheelchair access.....	5-37, 5-38, 5-71, 7-16
wheelchair space requirements.....	5-26
angle loading areas.....	4-12, 7-24
appearance, transit	
as quality of service factor.....	3-21
service standards.....	3-21
area, walkway.....	7-8
art.....	7-45
articulated bus	
<i>see</i> bus, articulated	
Atlanta, GA	
AGT.....	2-29
bus.....	2-5
heavy rail.....	2-20, 5-8, 5-25, 5-68, 5-69, 5-120
HOV lane.....	4-21
Auto Equivalent Units.....	6-6, 6-18
automated guideway transit	
capacity.....	5-55, 5-93
characteristics.....	5-13
door widths.....	5-23, 5-92
dwell time.....	5-92
example problems.....	5-101
headway, minimum.....	5-92, 5-93
illustrated.....	2-28
linear loading levels.....	5-38, 5-93
number of agencies, U.S.....	2-3, 2-27
off-line stations.....	5-93
operating environments.....	2-27, 5-91
passenger loads.....	5-92
performance, train.....	5-91
ridership, annual U.S.....	2-4
ridership, weekday by system.....	2-28, 2-29
right-of-way types.....	2-18, 5-57
sectioned power supply.....	5-91
signaling.....	5-91, 5-92
vehicles in maximum service, by system .	2-28
automated people movers	
<i>see also</i> automated guideway transit	
cable cars, relationship to.....	2-35
automatic train control	
capacity increase from.....	5-13
driver role.....	5-13
use.....	5-13
automatic train supervision	
description.....	5-14
predictive control.....	5-14
automation	
train control.....	5-11, 5-13
availability	
as quality of service factor	
... 1-7, 1-8, 3-2, 3-3, 3-6, 3-29, 3-31, 3-32, 3-37	
bicycles, effect of.....	3-9
capacity as factor.....	3-6, 3-16, 3-30
factors.....	1-8, 3-6, 3-7
headway, average.....	3-29
hours of service.....	3-31, 3-54
information.....	1-8, 3-6, 3-17
measures.....	1-9, 3-29, 3-30, 3-31, 3-32, 3-37
mode choice, relationship to.....	3-6
park-and-ride lots.....	3-13, 3-43
pedestrian crossing delay.....	3-40
response time.....	3-53
service coverage.....	3-32, 3-37
spatial.....	1-8, 3-6
temporal.....	1-8, 3-6

B

Baltimore, MD

- bus 5-9
- commuter rail 2-26, 5-8, 5-89
- heavy rail 2-20, 5-69
- light rail 2-23, 5-9, 5-17, 5-41
- station 2-41
- transit mall 5-9
- water taxi 6-2

Belo Horizonte, Brazil 4-22

benches 7-45

bicycle-friendly streets 3-12

bicycles

- access 3-30
- bikes-on-transit program 3-12
- curb extensions 4-29
- environment 3-12
- level of service 3-30
- lockers 3-13, 7-47
- parking 3-11, 3-12
- racks 3-13, 4-6, 7-47
- racks, bus-mounted 3-11, 3-12, 3-13
- service coverage, effect on 3-11, 3-12
- speed 3-12
- transit availability, effect on 1-8, 3-9, 3-11, 3-12
- trip lengths 3-12

blocks, city

- train length constraint 5-7, 5-8, 5-9, 5-71

blocks, signal 5-2, 5-11

boarding islands 4-11, 4-28

Bogotá, Colombia 4-22, 7-4

bollards 7-25

Boston, MA

- AGT 2-29
- BRT 2-16, 4-22
- bus 2-5, 2-13
- busway 4-21
- commuter rail 2-25, 2-26, 5-8, 5-89
- ferry 2-38, 2-40
- heavy rail 2-18, 2-20, 5-25
- HOV lane 4-21
- light rail 2-2, 2-24, 5-79
- passenger load standards 5-25
- streetcar 2-23

braking

- see performance, train

Brampton, ON 2-11

Bremerton, WA

- ferry 2-40
- signal priority 4-27

Brisbane, Australia

- busway 4-22, 4-43, 4-44
- ferry 2-37, 2-39, 6-7
- park-and-ride 4-43

BRT

- see Bus Rapid Transit

Budapest, Hungary 2-30

Buffalo, NY 2-23, 5-39

bunching 1-11, 3-17, 3-18, 3-47

bus

- accessibility 2-11
- articulated 2-11, 2-12, 4-18, 4-22, 4-39

bus (continued)

- BRT 2-15, 4-32
- busways 2-7, 2-8
- capacity **Part 4**
- comfort 2-11
- delay, sources of 4-24
- demand-responsive 2-5
- double-deck 2-11
- dwell time, effect of doors on 2-14
- exclusive right-of-way 2-7
- express service 2-5, 4-32
- fixed-route, described 2-5
- fleet size, U.S. 2-11, 2-12
- fuel 2-11, 2-12
- HOV lanes 2-9
- hybrid-electric 2-11
- limited-stop service 2-5, 4-32
- local service 2-5, 4-32, 4-45
- low-floor 2-11, 2-12, 4-18
- minibus 2-11
- mixed-traffic operation
 - 2-7, 2-10, 4-19, 4-24, 4-41, 4-57, 4-58, 4-59
- number of agencies, U.S. 2-3, 2-5
- operating practice 2-7
- over-the-road coach 2-12
- priority 2-14, 2-15
- ridership, annual U.S. 2-4
- ridership, selected routes 2-13
- ridership, top systems annual 2-5
- running time 4-52, 4-53
- skip-stop service 4-32, 4-33
- speed 4-46, 4-52, 4-53, 4-59
- standard 2-11, 2-12
- trolleybus 2-12
- vehicle types 2-11, 2-12, 4-18
- vehicles operated in maximum service,
 - selected routes 2-13
 - volumes 2-13, 2-14, 4-39
 - wheelchair access 2-11
 - see also wheelchairs

bus berths

- see loading areas

bus bridge 5-47

bus facilities 4-1, 4-3, 4-16, 4-20

bus lanes

- as priority measures 4-23, 4-37
- bus malls 2-9, 4-24, 5-31
- bus-bus interference factor 4-55
- capacity 4-40, 4-41, 4-47, 4-48, 4-49, 4-50, 4-51, 4-52, 4-53, 4-99
- concurrent flow 2-9
- contraflow 2-9, 2-14
- description 4-24
- development of 4-24
- exclusive 2-7, 2-9, 2-14, 4-24, 4-31, 4-37, 4-39, 4-40, 4-47, 4-50, 4-52, 4-53
- pedestrian impacts 4-48
- planning guidelines 4-37, 4-40, 4-41, 4-99
- right turns, effect of 4-12
- skip-stop operation 4-49, 4-50, 4-51, 4-53
- speed 4-52, 4-53, 4-54, 4-55
- types 4-47, 4-49, 4-57
- use by other vehicles 4-47, 4-48, 4-53
- vehicle capacity 4-97
- volumes, service 4-37

bus malls	
<i>see</i> bus lanes, bus malls	
Bus Rapid Transit	
benefits	2-15
described	2-15
fare collection	2-16
features	2-15
information, passenger	2-16
light rail, compared to	2-16
operating characteristics	2-15, 2-16
stations	2-15
systems, North American	2-16
vehicles	2-15
bus stops	
accessibility	2-42, 3-30, 3-37
amenities	2-42, 7-3
at terminals and transit centers	7-3
boarding islands	4-11, 4-28
busway stations	7-4
capacity	4-1, 4-2, 4-57
critical stop	4-2, 4-3, 4-16
defined	4-1
described	2-42
effect on capacity, loading area	4-41
effect on capacity, vehicles	2-13
flyer stops	4-12
illustrated	2-41
location factor	4-49, 4-58
locations	4-11, 4-12, 4-13, 7-3
off-line	4-7, 4-11
off-street	4-12
on-line	4-7, 4-11
on-street	4-11
pedestrian access	4-12
quality of service	3-29, 3-43
siting factors	4-12, 4-13
sizing	7-23, 7-24, 7-25
spacing guidelines	4-12
spacing, as dwell time factor	4-4
spacing, as speed factor	4-4, 4-46
transit stations	2-42
vehicle capacity	4-11, 4-12, 4-15, 4-99
waiting area	2-42, 7-23
waiting area level of service	7-23, 7-25
busways	
as transit priority measure	4-20, 4-22, 4-23
BRT	2-16
bus distribution	4-22
capacity	4-40, 4-41, 4-43, 4-44, 4-45
characteristics	4-21, 4-44
described	2-7, 2-8, 4-43
illustrated	2-9, 4-43
peak hour factors	4-45
planning guidelines	4-35, 4-36, 4-40, 4-41
speed, estimating	4-46
speed, typical operating	2-8
C	
cab control signaling	
described	5-12
dwell time estimation	5-24
line capacity	5-51
minimum train separation	5-59, 5-60, 5-63
cab control signaling (<i>continued</i>)	
person capacity	5-51, 5-52
reference speeds	5-12
throughput	5-63
cable car	
automated people movers,	
relationship to	2-35
conversion to streetcars	2-35
described	2-35
illustrated	2-35
number of agencies, U.S.	2-3
power	2-35
ridership, annual U.S.	2-4
speed	2-35
Calgary, AB	
bus	2-5, 5-9
light rail	2-2, 2-23, 2-24, 5-8, 5-9, 5-24,
.....	5-32, 5-33, 5-38, 5-66, 5-68, 5-69, 5-120
transit mall	5-9
capacity	
achievable	5-1, 5-2, 5-3, 5-4, 5-5, 5-31,
.....	5-34, 5-36, 5-49, 5-58, 5-79, 5-93
adjustment factor for adjacent lanes	4-50
agency policies, effect of	1-20
as quality of service factor	3-16
automated guideway transit	5-55, 5-93
automatic train control	5-13
bus	2-14, Part 4
bus facility	4-3, 4-11, 4-12, 4-16
bus lane	4-39, 4-40, 4-41, 4-47,
.....	4-48, 4-49, 4-50, 4-51, 4-52, 4-53, 4-99
bus stop	4-1, 4-2, 4-11, 4-12, 4-15, 4-41, 4-57
busway	4-40, 4-41, 4-43, 4-44, 4-45
cab signaling	5-51
car	5-25, 5-26, 5-27, 5-29
commuter rail	
.....	5-55, 5-81, 5-83, 5-84, 5-85, 5-86, 5-87
crush	5-26
defined	1-14
demand-responsive	4-62, 4-63
design	5-1, 5-5, 5-49, 5-74
doorway	7-31, 7-32
dwell time, effect of	1-18
economic constraints	1-20
elevator	7-38, 7-39, 7-40
escalator	7-35, 7-36
factors	1-18, 1-19, 1-20, 4-41, 4-42, 4-47, 4-51
fare gate	7-42
ferry	Part 6
grade-separated rail	
.....	5-57, 5-58, 5-59, 5-64, 5-66, 5-67, 5-68, 5-69
heavy rail	<i>see</i> capacity, grade-separated rail
HOV lane	4-45
inclined plane	2-30
influence of growth	5-49
light rail	5-71, 5-72, 5-74, 5-76, 5-78
line	5-2, 5-3, 5-5, 5-9, 5-69
loading areas	4-2, 4-3, 4-8, 4-9, 4-10, 4-41, 7-25
loading diversity, effect of	1-20
mature	5-49
maximum schedule load	4-17
mixed traffic, bus	4-57, 4-58
monorail	2-29
moving walkway	7-37
moving-block signaling	5-51

capacity (<i>continued</i>)	
overview	1-13, 1-14
pedestrian	7-7, 7-10, 7-20, 7-32
person	1-14, 1-15, 1-16, 1-20, 1-21, 4-3, 4-16, 4-39, 4-40, 4-41, 5-5, 5-9
planning applications, bus	4-35, 4-38, 4-39, 4-40, 4-41, 4-99
planning applications, rail	5-49, 5-50, 5-51
planning applications, ropeway	5-55
productive	1-21
ramp	7-40
rail	Part 5
reliability, relationship to	1-13
right-of-way types, effect of	1-19
ropeway	5-55, 5-95, 5-96
skip-stop operation	4-49, 4-50
special events	1-14
speed, relationship to	1-13
stairway	7-12, 7-13, 7-33, 7-34
supply constraints	5-5
terminal	5-3, Part 7
traffic signals, effect of	4-10
train, theoretical	5-5
vehicle	1-14, 1-15, 1-16, 1-17
vehicle characteristics, effect of	1-19
walkway	7-8, 7-9, 7-29, 7-30
ways to improve	4-41, 4-42, 4-52
weakest link	5-57, 5-58, 5-71
captive riders	2-1
car capacity	5-25, 5-26, 5-27, 5-29
cars, rail	
bi-level	2-26, 5-26, 5-70, 5-85, 5-89
effect on design capacity	5-5, 5-6
passenger loads	5-5, 5-6, 5-26
seating configurations	5-26, 5-27
catamarans	6-2
Chattanooga, TN	2-12, 2-31, 2-32
Chicago, IL	
AGT	2-29
bus	2-5
bus mall	2-13
commuter rail	2-25, 2-26, 2-27, 5-8, 5-44, 5-68, 5-69, 5-81, 5-83, 5-85, 5-89, 5-120
ferry	2-40
heavy rail	2-18, 2-19, 2-20, 5-8, 5-25, 5-35, 5-68, 5-69, 5-120
HOV lane	4-21
park-and-ride	3-13
passenger load standards	5-25
ridership	2-2
signal priority	4-27
skip-stop rail operations	5-35
Chillicothe, MO	2-13
choice riders	2-1, 3-13, 3-29
Cincinnati, OH	2-29
circulation	
pedestrian	7-19, 7-20, 7-21
clearance time	
defined	4-2, 4-7
effect on capacity	4-2
estimating	4-7
ferry	6-10, 6-11, 6-13, 6-18
light rail	5-76
off-street bus stops	7-25
re-entry delay	4-7
Cleveland, OH	
BRT	4-22
bus	2-12
heavy rail	2-18, 2-19, 2-20
light rail	2-22, 2-23, 5-37, 5-41
park-and-ride	7-47
close-in time	5-13, 5-14, 5-58, 5-64
coefficient of variation	
dwell times	4-8, 5-76
ferry embarking and disembarking time	6-13
headway	3-48, 5-33
comfort and convenience	
amenities	1-9, 3-45
appearance of transit	1-9
as quality of service factor	1-7, 1-8, 3-2, 3-3, 3-6, 3-21, 3-43, 5-67, 6-2, 6-3
bus stop consolidation	4-32
demand-responsive service	3-58, 3-59, 3-60
factors	1-9, 3-6
measures	1-9, 3-43, 3-45, 3-48, 3-49, 3-51, 3-58, 3-59
out-of-pocket cost	1-9
passenger loading	1-9
reliability	1-9, 3-45, 3-56
safety and security	1-9, 3-45, 3-51
transfers	1-9
transit-auto travel time	3-49, 3-50, 3-51, 3-59
travel speed	3-49
travel time	1-9, 3-51, 3-58
wait assessment	3-49
commuter rail	
bi-level car	2-26
capacity	5-50, 5-55, 5-57, 5-70, 5-81, 5-83, 5-84, 5-85, 5-86, 5-87
comfort	2-25
described	2-24, 2-25
dwell times	5-84, 5-85
example problem	5-101
express service	5-82, 5-83
fare collection	7-41
freight railroad relationships	2-24, 5-81, 5-82
illustrated	2-24
North American cars	5-88
number of agencies, North America	2-26
number of agencies, U.S.	2-3
park-and-ride	2-27
passenger boarding	2-26
passenger loads	2-25, 5-68, 5-84, 5-88, 5-120
peak hour factor, default	5-68
peak hour factor, selected systems	5-68, 5-69
person capacity	5-88
platform height	2-26, 5-85
platform length	5-88
power	2-25, 5-81, 5-87, 5-88
priority level	5-82
ridership, annual U.S.	2-4
ridership, peak 15 minutes	2-27
ridership, peak hour	2-27
ridership, weekday system	2-26
right-of-way types	2-18, 5-57
seating arrangements	2-25, 5-88
speed, average	5-87
standees	5-88
train length	2-25, 5-88
train storage	5-84

commuter rail (*continued*)
 train throughput
 5-50, 5-55, 5-57, 5-70, 5-81, 5-83
 vehicle types2-25, 5-55, 5-81, 5-85
 vehicles in maximum service, by system..2-26
 wheelchair access.....5-44
 contraflow operation..... 2-9, 2-14
 convenience
 see comfort and convenience
 Copenhagen, Denmark.....4-28
 Corpus Christi, TX.....2-40
 cost
 as quality of service factor.....3-21
 out-of-pocket3-21
 crew turnaround time.....5-17
 critical gap, pedestrian3-41
 critical stop4-2, 4-32, 4-51
 crush loads... 3-30, 3-45, 4-17, 5-6, 5-26, 5-28, 5-29
 curb extensions4-29
 Curitiba, Brazil 4-22, 7-4
 customer satisfaction surveys
 *see* surveys, customer satisfaction
 customer service3-7

D

Dallas, TX
 AGT.....2-29
 busway4-21
 commuter rail 2-25, 2-26
 HOV lane4-21
 light rail2-23
 ridership2-2
 deceleration4-46
 Delaware River Port Authority2-33
 delay
 ferry.....6-14
 pedestrian3-11, 3-40, 3-41, 3-42
 person5-5
 re-entry 4-7, 4-30, 4-57
 transit priority benefits4-19
 demand-responsive service
 ADA2-6, 2-7, 3-53, 4-61
 capacity..... 4-62, 4-63
 comfort and convenience3-58, 3-59, 3-60
 complementary 2-7, 4-61
 demand..... 4-62, 4-63
 described2-5, 3-53, 3-56, 4-61
 dwell time 3-57, 4-62
 environmental factors4-61
 hours of service 3-54, 3-55
 level of service
 3-53, 3-54, 3-55, 3-57, 3-58, 3-59, 3-60
 lifeline service.....3-55
 number of agencies, U.S.2-3
 on-time performance..... 3-56, 3-57
 operating types2-5, 2-6, 4-61, 4-63
 policy, effect of 4-61, 4-62, 4-63
 quality of service.....1-11, 3-3, 3-53, 3-54
 quality of service framework..... 1-9, 3-53
 reliability 3-56, 3-57
 response time.....3-53, 3-54, 4-61
 ridership characteristics.....4-61
 ridership, annual U.S.2-4, 2-6

demand-responsive service (*continued*)
 scheduling 4-63
 service area..... 4-63
 service types.....4-61, 4-63
 shared rides, effect of..... 3-59
 subscription service 3-53
 time windows 3-56, 3-57
 travel time.....3-58, 3-59, 3-60
 trips not served.....3-57, 3-58
 vehicle types.....2-11, 4-62
 wait time 4-62
 density, pedestrian7-7, 7-8, 7-9
 Denver, CO
 AGT 2-29
 bus2-12, 2-13
 bus lane..... 4-47
 bus mall.....2-9, 2-10, 4-24
 escalator 7-35
 hybrid-electric bus 2-11
 kiss-and-ride 7-48
 light rail..... 2-23, 2-24, 5-8, 5-41, 5-69, 5-74
 station amenities..... 7-46
 ticket machine 7-43
 Detroit, MI.....2-27, 2-28, 2-29, 5-91, 5-93
 deviated route service 2-7
 disabled trains, effect on system operation
 5-45, 5-46
 discrete choice models 1-11
 distance, air 3-37
 distance, walking 3-9, 3-10, 3-33, 3-37
 diversity, loading 5-5, 5-6, 5-7, 5-67, 5-93, 5-97
 doors
 AGT 5-92
 cycle times, rail 5-35
 passenger-actuated 5-35
 doorways, terminal
 capacity7-31, 7-32
 effect on pedestrian flow..... 7-31
 number of7-31, 7-32
 width 7-32
 driver, train
 effect on minimum headway 5-12
 role in automatic train operation..... 5-13
 drive-through loading areas4-12, 7-24
 dwell time
 bicycle loading, effect of..... 4-4, 4-6
 bus capacity, effect on4-2, 4-3, 4-8
 calculation5-23, 5-66
 coefficient of variation..... 4-8, 5-76
 commuter rail5-84, 5-85, 7-5
 components5-3, 5-19
 controlling 5-2, 5-19, 5-24, 5-64
 data collection procedure.....4-93, 4-94, 4-95
 demand-responsive service.....3-57, 4-62
 doors, effect of 5-23
 estimating, bus.....4-4, 4-5, 4-6
 estimating, rail.....5-23, 5-24, 5-64, 5-65, 5-66
 factors. 1-18, 1-19, 4-2, 4-3, 4-4, 4-11, 4-14, 5-23
 fare collection, effect of..... 1-10
 loading area design, effect of..... 4-14
 minimum rail headway, effect on
 5-3, 5-4, 5-14, 5-24
 passenger loads, effect of 4-17
 pedestrian time-space..... 7-16
 speed, effect on4-46, 4-52, 4-59

dwelt time (*continued*)
 traffic signal timing, effect of 4-10
 variability 4-2, 4-4, 4-8, 4-9, 5-3
 wheelchairs, effect of ..4-4, 4-6, 5-37, 5-42, 5-43

E

Edmonton, AB 2-21, 2-23, 2-24, 5-24
 elasticity 1-11, 1-12
 elevators
 as public transportation 2-31
 boarding and alighting time 7-39
 capacity 7-38, 7-39, 7-40
 illustrated 7-38
 level of service 7-39
 maintenance 7-38
 operating characteristics 7-40
 out of service 7-38
 space per pedestrian 7-39, 7-40
 travel time 7-40
 wait time 7-39
 emergency exits 5-36
 empty lane syndrome 1-15, 2-9
 environment, bicycle
 see bicycles, environment
 environment, pedestrian
 see pedestrian, environment
 escalators
 capacity 7-35, 7-36
 dimensions 7-35, 7-36
 emergency use 5-36, 7-17, 7-18, 7-36
 flow rate 5-36
 number of 7-36
 queuing area 7-35, 7-36
 speed 7-35
 stairways, supplement to 7-33, 7-34
 utilization 7-35
 wait time 7-36
 Essen, Germany 2-8
 Eugene, OR 4-22
 evacuation ..5-36, 7-17, 7-30, 7-32, 7-34, 7-36, 7-41
 example problems
 bus capacity 4-69 to 4-89
 ferry capacity 6-21 to 6-25
 quality of service 3-65 to 3-91
 rail capacity 5-101 to 5-116
 stop, station, and terminal capacity
 7-51 to 7-66
 exclusive bus lanes
 see bus lanes, exclusive
 exclusive right-of-way, rail 5-9
 express service
 BRT 2-16
 bus 4-32
 commuter rail 5-83
 heavy rail 5-35
 light rail 5-35

F

failure rate
 bus capacity, influence on 4-2
 defined 4-2, 4-8
 operating margin 4-8, 4-9

failure rate (*continued*)
 quality of service, effect on 4-9
 speed, effect on 4-9
 values 4-9
 fare collection
 as quality of service factor 1-10
 BRT 2-16
 bus 2-13
 distance-based fares 7-41
 effect on capacity 6-15
 effect on dwell time 1-10, 4-4, 5-36
 ferry 6-6, 6-7, 6-10, 6-12, 6-13, 6-16
 magnetic stripe tickets 7-41
 on-board fare machines 5-36, 5-37
 proof-of-payment 4-42
 ticket booths 7-43
 ticket machines 7-43, 7-44
 fare gates
 ADA 7-41
 capacity 7-42
 described 7-41
 emergency use 5-36
 headway 7-42
 illustrated 7-41
 maintenance 7-42
 number of 7-42
 pedestrian flow, effect on 7-41
 types 7-41
 volume-to-capacity ratio 7-42
 ferries
 access 6-9
 AEUs 6-6
 applications 2-37
 capacity **Part 6**
 clearance time 6-10, 6-11, 6-13, 6-18
 coastal services 2-38
 comfort 6-3
 demand, peaking characteristics of 2-38
 demand, total passenger/auto 6-11
 described 2-37
 draft requirements 6-2, 6-3
 en route stops 6-18
 fare collection 6-6, 6-7, 6-10, 6-12, 6-13, 6-16
 fuel usage 6-2, 6-3, 6-4
 gangway technology 6-11, 6-12
 harbor traffic, influence of 6-11, 6-12
 headway, between vessels 2-38, 6-18
 headway, entering/exiting vehicles 6-16
 illustrated 2-39
 intermodal transfers 2-37, 2-38, 6-1
 licensing issues 6-18
 loading 6-4, 6-5, 6-6, 6-7, 6-10, 6-18
 maintenance 6-2, 6-3
 mixed embarking and disembarking 6-16
 mooring procedures 6-11, 6-12
 number of agencies, U.S. 2-3
 operating costs 6-4
 overhead factor 6-6
 passenger loading 6-7, 6-8
 peak hour factor 6-18
 propulsion 6-4
 ridership, annual U.S. 2-4
 ridership, weekday North America 2-40
 rural services 2-38
 safety 6-8, 6-9

ferries (*continued*)

- service time, arrival6-10, 6-11, 6-12, 6-13, 6-14, 6-16
- service time, departure6-10, 6-11, 6-12, 6-13, 6-14, 6-16
- service time, influence of fare collection...6-12
- service types2-37, 2-38, 6-1, 6-2
- speed, entering/exiting vehicles.....6-16
- speed, passengers6-15
- speed, vessel6-2, 6-3, 6-4
- staging area.....6-5, 6-6
- terminals6-4, 6-5, 6-6, 6-7, 6-9, 6-10, 6-12, 6-13, 7-5
- travel time2-38, 6-3, 6-4, 6-7, 6-10
- urban services.....2-38, 6-1
- variation of embarking and disembarking time6-13
- vehicle loading.....2-38, 6-1
- vessels.....2-38, 6-3, 6-6
- vessels in maximum service, North American systems2-40
- water taxi.....2-38, 6-1

fixed-block signal systems

- described5-11
- driver precision required.....5-12
- minimum train separation5-63
- overlay systems.....5-11
- safety.....5-11, 5-13
- signal aspects.....5-11
- throughput.....5-11, 5-51, 5-63

fixed-route service

- quality of service framework.....1-9

flat junctions.....5-4, 5-14, 5-17

floor height5-19, 5-21, 5-22, 5-40

flow, pedestrian.....6-15, 7-7, 7-8, 7-10, 7-30, 7-31

flying junctions5-4, 5-14, 5-17

frequency

- see also* headway
- as quality of service factor1-10, 1-11, 3-16, 3-29, 3-30
- capacity, influence on.....4-17, 4-18
- ferry.....6-18
- levels of service3-29, 3-30
- relationship to passenger loads2-13

fuel

- see also* power
- ferry.....6-3

funicular railway

- see* inclined plane

funitel

- see* ropeways

G

- Galveston, TX.....2-23
- gauntlet track5-72
- GIS.....3-32, 3-33, 3-34, 3-35, 3-42
- glossary**Part 8**
- gondola
- see also* ropeways
- capacity.....5-56
- wheelchair access.....5-45

grade

- effect on headway5-59, 5-62, 5-63
- planning assumption.....5-49

grade crossings...2-18, 2-42, 5-71, 5-76, 5-77, 5-85

grades, maximum2-32

grade-separated operation

-5-57, 5-58, 5-59, 5-64, 5-66, 5-67, 5-68, 5-69

green time ratio4-10

growth, relation to capacity5-49

guided busway

- see* busway, guided

H

- Haifa, Israel.....2-30
- hail-and-ride2-42
- Halifax, NS.....2-40
- Hartford, CT2-40
- headway
- see also* frequency
- adherence3-18, 3-45, 3-47, 3-48, 5-31, 5-33
- clock headways.....3-29
- coefficient of variation.....5-33
- components.....5-4, 5-31, 5-33
- ferry6-16, 6-18
- minimum5-2, 5-3, 5-4, 5-14, 5-17, 5-18, 5-19, 5-54, 5-58, 5-63, 5-69, 5-72, 5-76
- non-interference headway5-14
- policy.....5-25

heavy rail

- capacity**Part 5**
- described.....2-18, 2-19
- dominance of New York2-19
- doors.....5-35
- express service5-35
- fare collection.....7-41
- grade crossings2-18
- illustrated.....2-19
- linear loading levels.....5-38, 5-67
- number of agencies, U.S.2-3
- park-and-ride2-19
- passenger boarding.....5-19, 5-20, 5-21, 5-22
- passenger loads5-25, 5-26, 5-28, 5-29, 5-30
- peak hour factor, default.....5-68
- peak hour factor, selected systems.....5-7, 5-8
- power2-18
- pre-war and postwar systems.....2-19
- ridership, annual U.S.....2-4
- ridership, peak 15 minutes2-21
- ridership, peak hour2-20, 2-21
- ridership, weekday system.....2-20
- right-of-way types.....2-18, 5-57
- skip-stop operations5-35
- vehicles in maximum service, by system. 2-20

Heidelberg, Germany2-30

Highway Capacity Manual1-7, 1-14, 3-1, 3-5, 3-22, 3-39, 3-62, 4-3, 4-7, 4-35, 4-45, 4-46, 4-48, 4-50, 4-57, 4-58, 7-7, 7-10, 7-14, 7-23

Hong Kong, China2-21, 2-30, 2-37, 6-2

Honolulu, HI

- BRT2-16
- bus-mounted bicycle rack.....3-13
- HOV lane.....4-21
- monorail.....2-28, 2-29

hours of service3-16, 3-29, 3-54
 as quality of service factor3-31, 3-54
 calculated.....3-31, 3-32, 3-54
 demand-responsive3-54, 3-55
 examples 3-32
 express vs. local service..... 3-31
 fixed-route 3-31
 levels of service.....3-31, 3-54, 3-55
 Houston, TX
 AGT 2-29
 bus 2-5
 bus lane 4-48
 HOV lanes 4-21, 4-22, 4-23
 light rail..... 2-23
 park-and-ride 7-47
 HOV lanes
 bus distribution 4-22
 capacity 4-45
 characteristics, selected facilities 4-21
 concurrent flow 2-9
 contraflow 2-9
 described.....2-9, 4-20, 4-23, 4-43, 4-45
 empty lane syndrome..... 2-9
 facility types 2-9
 illustrated.....2-9, 4-23, 4-46
 level of service 4-45
 planning guidelines 4-35
 service volume..... 4-45
 speed, estimating..... 4-46
 hovercraft 6-3
 Huntsville, AL 2-29
 hybrid low-floor car 5-40
 hybrid signal systems..... 5-13
 hydrofoils 6-3

I

impedance factor, adjacent lane 4-49
 inclined plane
 applications2-30, 5-95
 capacity2-30, 5-55
 described..... 2-30
 illustrated..... 2-31
 number of agencies, U.S..... 2-3
 relationship to elevators..... 2-31
 ridership, annual U.S..... 2-4
 ridership, weekday 2-32
 track types 2-30
 vehicle types..... 2-30
 wheelchair access 5-45
 worldwide use 2-30
 information
 as quality of service factor 3-17
 automatic train supervision..... 5-14
 availability, effect on..... 3-17
 displays 3-17
 Internet..... 3-17
 on-board announcements 3-17
 printed..... 3-17
 public address systems..... 7-45
 real-time 3-17, 7-45
 signs..... 3-17, 7-18, 7-44
 Intelligent Transportation Systems..... 2-16
 intercity service 2-7

J

Jackson, WY 2-33
 Jacksonville, FL
 AGT 2-28
 monorail 2-29
 Japan 2-30
 Jersey City, NJ 2-23, 5-40
 jitneys 2-7
 Johnstown, PA 2-30, 2-31, 2-32
 inclined plane 5-45
 junctions
 effect on minimum headway
 5-4, 5-14, 5-17, 5-18, 5-57, 5-79
 flat 5-4, 5-14, 5-17
 flying 5-4, 5-14, 5-17
 throughput..... 5-14, 5-17
 with moving-block signals..... 5-14, 5-18, 5-57

K

Kenosha, WI 2-23
 Ketchikan, AK 2-30, 2-31
 kiss-and-ride..... 2-42, 5-36, 7-48

L

Larkspur, CA 3-13
 Las Vegas, NV
 AGT 2-29
 monorail 2-29
 Lausanne, Switzerland 2-30
 layover, terminal 5-15, 5-16, 5-17, 5-34
 level of service
 availability 3-29, 3-31, 3-32
 comfort 3-43
 defined..... 3-2
 demand-responsive, DRT-auto travel time
 3-59, 3-60
 demand-responsive, hours of service
 3-54, 3-55
 demand-responsive, on-time performance
 3-57
 demand-responsive, response time 3-53, 3-54
 demand-responsive, trips not served 3-58
 development of thresholds 3-22
 elevator..... 7-39
 frequency 3-29
 headway adherence..... 3-47, 3-48
 hours of service 3-31, 3-54
 on-time performance..... 3-46, 3-47, 3-56
 passenger loads 3-43, 3-45
 pedestrian
 7-1, 7-7, 7-8, 7-11, 7-13, 7-29, 7-31, 7-33
 queuing area 7-14, 7-15, 7-26, 7-28
 reliability 3-45, 3-46, 3-47, 3-56
 service coverage..... 3-32, 3-34
 stairway 7-13, 7-14
 standing passenger area 3-45
 transit-auto travel time 3-49, 3-50
 waiting area 7-14, 7-15, 7-23, 7-25, 7-29
 walkway 7-10, 7-11, 7-30
 lifeline service 3-55

lifts	
car-mounted	5-42
platform-mounted	5-43
light rail	
capacity	
...5-53, 5-54, 5-57, 5-71, 5-72, 5-74, 5-76, 5-78	
clearance time	5-76
coefficient of variation of dwell times	5-76
described	2-21
diesel	2-21
doors, passenger-actuated	5-35
example problem	5-101
fare collection	7-41
frequency, North American lines	2-24
headway, North American lines	2-24
illustrated	2-22
lifts	5-42, 5-43
linear loading levels	5-67
low-floor vehicles	5-38, 5-39, 5-40
number of agencies, North America	2-23
number of agencies, U.S.	2-3
on-demand stops	5-35
on-street operation	5-54, 5-74, 5-75
passenger boarding	5-19, 5-21, 5-22
passenger loads	5-25, 5-27, 5-28, 5-29
peak hour factor, default	5-68
peak hour factor, selected systems	5-69
power	2-21
pre-war and postwar systems	2-23
ridership, annual U.S.	2-4
ridership, peak 15 minutes	2-24
ridership, peak hour	2-24
ridership, weekday system	2-23
right-of-way types	2-18, 2-21, 5-53, 5-71
single-track operation	5-53, 5-72, 5-73
streetcars	2-22
vehicles in maximum service, by system	2-23
vintage trolleys	2-22
wheelchair access	
.....5-38, 5-39, 5-41, 5-42, 5-43, 5-71	
lighting	3-10
limited-stop service	4-32
Lincoln Tunnel	
..... 2-2, 2-9, 2-13, 2-14, 4-21, 4-23, 4-45	
line capacity	
automatic train control, effect on	5-13
calculating	
..... 5-58, 5-59, 5-64, 5-66, 5-67, 5-68, 5-69	
factors	5-2, 5-3
planning applications, AGT	5-55
planning applications, rail	
..... 5-49, 5-50, 5-51, 5-54, 5-55	
planning applications, ropeway	5-55, 5-56
relationship to design capacity	5-5
linear loading areas	4-12, 4-14, 7-24
linked trips	2-3
Little Rock, AK	2-23
load factor	3-18, 3-43
loading areas	
at terminals and transit centers	7-24
capacity	4-2, 4-3, 4-8, 4-9, 4-10, 4-41, 7-25
defined	4-1
dwell time	4-3
effect on bus stop capacity	4-14
effectiveness	4-12, 4-14, 4-99
loading areas (continued)	
ferry	6-4, 6-5, 6-6, 6-7, 6-9, 6-10, 6-12
number of	4-11, 4-12, 4-14
pedestrian circulation	7-25
planning guidelines	4-41
safety	7-25
size	4-11
types	4-12, 4-14, 7-24
loading diversity	5-5, 5-6, 5-7, 5-67, 5-93, 5-97
<i>see also</i> passenger loads <i>and</i> peak hour factor	
loading height	
<i>see</i> passenger boarding, service standards	
loading standards	
<i>see also</i> floor height	
Local Index of Transit Availability	3-42
local service	2-16, 4-32, 4-45
location factor, bus stop	4-49, 4-58
London, United Kingdom	
ferry	2-37
heavy rail	5-16, 5-28
Long Island Rail Road	2-25
Los Angeles, CA	
AGT	2-29
bi-level rail car	2-26
BRT	2-16, 4-22, 4-32
bus	2-5, 2-10
commuter rail	2-26, 5-8, 5-44, 5-82, 5-89
escalator	7-35
funicular	2-32
heavy rail	2-20, 5-58
HOV lane	4-21
inclined plane	5-45
light rail	2-23, 2-24, 5-38, 5-76
signal priority	4-27
low-floor vehicles	
as dwell time factor	1-10
bus	2-11, 2-12, 4-18
hybrid	5-40
light rail	5-37, 5-38, 5-39, 5-40
LRT	
<i>see</i> light rail	

M

magnetic stripe tickets	7-41
maintenance	1-8, 3-8, 5-46, 6-2, 6-3, 7-38
Maple Ridge, BC	2-13
market shed analysis	3-15
mature capacity	5-49
maximum load section	
..... 2-23, 4-16, 4-17, 4-45, 5-31, 5-58	
maximum load segment	1-16
maximum schedule load	4-17, 4-18, 5-28
median operation	5-77
Memphis, TN	
monorail	2-29
vintage trolley	2-22, 2-23
Mexico City	5-25
Miami, FL	
AGT	2-28, 2-29, 5-23, 5-91, 5-93
BRT	2-16
bus lane	4-47
busway	2-8, 4-22
commuter rail	2-26, 5-89

Miami, FL (continued)

- heavy rail 2-20, 5-8
- HOV lane 4-21
- stairway 7-32
- micro-peaking 2-41, 7-29

Minneapolis, MN

- AGT 2-29
- bus mall 2-9
- busway 4-21
- light rail 2-23, 5-40

mixed-traffic operation

- adjustment factor 4-57, 4-58
- bus 2-10, 4-41, 4-57, 4-58, 4-59
- illustrated 2-10
- lane types 4-57
- person capacity 4-58
- speed 4-59
- vehicle capacity 4-41

model, transportation planning
..... 3-50, 5-49, 5-59, 5-66

monohulls 6-2

monorail

- capacity 2-29
- described 2-29
- illustrated 2-30
- number of agencies, U.S. 2-3
- ridership, annual U.S. 2-4

Montréal, QC

- BRT 2-16
- bus 2-5
- bus lane 4-24, 4-47
- commuter rail 2-26, 5-8, 5-81, 5-85, 5-89
- heavy rail 2-19, 2-20, 5-8, 5-25, 5-69
- HOV lane 4-21
- passenger load standards 5-25
- yield-to-bus 4-30

Morgantown, WV 2-28, 2-29, 5-93

Moscow, Russia 5-11

moving walkways 7-37, 7-38

moving-block signaling system
..... 5-12, 5-13, 5-18, 5-63

N

National Transit Database 1-7, 2-3, 3-5

neo-traditional development 2-2

New Haven, CT

- commuter rail 2-26, 5-83

New Jersey

- bus 2-5, 2-7, 2-13
- bus lane 2-9, 2-14
- commuter rail
.. 2-25, 2-26, 5-44, 5-81, 5-82, 5-84, 5-85, 5-89
- heavy rail 5-8, 5-24
- HOV lane 4-21
- light rail 2-21, 2-23, 5-40

New Orleans, LA

- car-mounted lift 5-43
- ferry 2-40
- streetcar 2-23

New York, NY

- aerial tramway 2-33, 2-34
- AGT 2-29
- bus 2-5, 2-13, 2-14

New York, NY (continued)

- bus lane 2-9, 2-10, 2-13, 4-47, 4-97
- commuter rail 2-25, 2-26, 2-27, 5-7, 5-8, 5-44,
5-68, 5-69, 5-81, 5-82, 5-83, 5-84, 5-89, 5-120
- farecards 7-41
- ferry 2-37, 2-38, 2-39, 2-40, 6-1, 6-4, 6-12, 6-18
- heavy rail 2-19, 2-20, 2-21, 5-7, 5-8,
5-17, 5-19, 5-24, 5-25, 5-32, 5-33,
5-35, 5-47, 5-66, 5-68, 5-69, 5-120
- Lincoln Tunnel 2-2, 2-13
- passenger load standards 5-25
- Port Authority Bus Terminal 7-24
- ridership 2-2
- terminals 5-84
- wait assessment 3-49

Newark, NJ

- airport loading area 7-24
- bus 2-13
- commuter rail 5-8, 5-69
- heavy rail 5-21, 5-32, 5-33, 5-66
- light rail 2-23, 2-24, 5-40
- monorail 2-28, 2-29

NFPA 130 requirements 5-36, 7-17, 7-18,
7-26, 7-30, 7-32, 7-34, 7-36, 7-38, 7-41

Niagara Falls, ON 2-32, 2-34

non-interference headway 5-14

non-linear loading areas 4-12

Norfolk, VA 2-40

O

Oakland, CA

- BRT 2-16
- HOV lane 4-21

off-line stops

- AGT 5-50, 5-92, 5-93, 5-101
- as clearance time factor 4-7, 4-11
- bus 4-11, 4-41, 4-45, 4-46, 4-54, 4-57, 4-58

Olympia, WA 3-13

- loading area 7-24
- transit center 2-41

on-demand stops 5-35

on-line stops

- as clearance time factor 4-7
- bus 4-11

on-street operation, light rail
..... 5-40, 5-54, 5-57, 5-71, 5-74, 5-75

on-time performance

- see also reliability
- as quality of service factor 3-47, 3-56, 3-57
- calculated 3-56
- Canadian vs. U.S. standards 3-46
- demand-responsive service 3-56, 3-57
- described 3-56
- early running 3-46
- levels of service 3-47, 3-57
- measurement locations 3-47
- reliability 3-56

operating margin 4-8, 4-9, 5-3, 5-14, 5-18, 5-19,
5-31, 5-33, 5-34, 5-38, 5-66, 5-67, 5-73, 5-93

operating practices

- effect on capacity 5-19, 5-35, 5-58
- effect on speed 4-44

Oregon City, OR 2-31, 2-32

Orlando, FL
 AGT..... 2-29, 5-92
 bus lane.....4-47
 Ottawa, ON
 BRT..... 2-16
 bus..... 2-13
 busway 2-8, 4-21
 HOV lane4-21
 light rail 2-21, 2-23

P

Palm Beach, FL.....6-4
 paratransit
 see demand-responsive service
 Paris, France
 flying junction5-4
 heavy rail.....5-17
 inclined plane2-30
 park-and-ride
 access 3-13, 3-14, 3-30
 busway4-44
 characteristics of successful lots 3-13, 3-14
 demand.....7-47
 facilities..... 3-14, 3-15, 7-47
 ferries 2-38, 6-1
 heavy rail..... 2-19
 illustrated 4-43, 7-47
 influence on ridership..... 2-27, 5-36
 market areas 3-15, 4-21
 mature capacity5-49
 percent persons served3-43
 service coverage 3-37, 3-43
 service coverage, effect on..... 1-8
 stops, stations, and terminals..... 2-41, 2-42
 transit-oriented development7-47
 user characteristics3-13
 parking
 bicycle 3-11, 3-12
 bus stop location, influence on.....4-12
 restrictions.....4-31
 passageways.....5-36
 passenger boarding
 as dwell time component ..4-3, 4-17, 5-19, 5-20
 boarding positions, bus2-13
 commuter rail5-44, 5-84, 5-85
 door widths.....5-23
 floor heights.....5-19
 frequency.....2-13
 heavy rail.....5-38
 loading height5-38
 multiple doors, bus.....2-16
 multiple doors, rail5-23
 multiple stops, bus2-13
 service times5-19, 5-20, 5-21, 5-22
 passenger demand
 as dwell time factor 4-3, 4-8, 4-17
 effect on ferry operations..... 6-7, 6-10
 passenger environment surveys .. 3-25, 3-26, 3-45
 passenger loads
 as quality of service factor
 3-18, 3-43, 3-44, 5-25, 5-26, 5-29, 5-30
 capacity, effect on 5-5, 5-25, 5-26

passenger loads (*continued*)
 commuter rail
 5-25, 5-26, 5-30, 5-84, 5-88, 5-117
 crush loads4-17, 5-26, 5-28, 5-29
 dwell time, effect on3-43, 4-4, 4-17
 equivalent passengers 3-44
 guidelines4-40, 5-25, 5-26, 5-29, 5-30
 heavy rail..... 5-67
 levels of service.....3-43, 3-44, 3-45
 light rail..... 5-25, 5-27, 5-28, 5-29, 5-67, 5-79
 linear loading levels
 5-25, 5-26, 5-28, 5-29, 5-30, 5-67
 load factor3-18, 3-43, 3-45
 major U.S. rail trunks..... 5-29, 5-67
 maximum schedule load 4-17
 personal space requirements..... 5-26
 rail, general..... 5-25
 reliability, effect on 3-43
 service disruptions, effect of..... 5-7
 service standards3-18, 5-25
 short turns, effect on train loading..... 5-7
 special events5-22, 5-43, 5-47
 standing passenger area3-43, 3-44
 standing time, maximum..... 5-25
 travel time, effect on 3-43
 variations between cars of a train..... 5-6
 variations within a car 5-5, 5-28
 wheelchair provisions 5-26, 5-28
 passenger service times
 bus 4-5, 4-6
 data collection procedure.....4-93, 4-94
 door width, effect of 4-5, 4-6, 5-3, 5-23
 fare collection, effect of..... 5-36
 ferry6-6, 6-10, 6-12
 rail5-3, 5-19, 5-22
 special events5-22, 5-47
 wheelchair5-37, 5-38, 5-41, 5-42, 5-43
 passenger waiting area6-12, 7-23
 passing sections..... 5-73
 pass-ups.....1-17, 3-16, 3-29, 3-32, 5-5
 peak hour factor 4-3, 4-5, 4-17, 4-18, 4-40, 5-6,
 5-7, 5-9, 5-25, 5-28, 5-37, 5-68, 5-88, 6-18
 see also loading diversity
 pedestrian
 access 3-30
 buffer width7-9, 7-23, 7-30
 capacity7-7, 7-10, 7-20, 7-32
 characteristics.....7-7, 7-14, 7-20, 7-23, 7-31
 circulation7-19, 7-20, 7-21
 comfort and convenience
 7-7, 7-8, 7-12, 7-14, 7-26, 7-28
 conflicts7-8, 7-9, 7-12, 7-33
 critical gap 3-41
 crossing difficulty..... 3-30
 curb extensions 4-29
 delay3-11, 3-39, 3-40, 3-41, 3-42
 demand 7-29
 density7-7, 7-8, 7-9
 doorways 7-31
 end clearance time 3-41
 environment.....1-8, 3-10, 4-32, 7-9, 7-29
 flow 5-36, 7-7, 7-8, 7-10, 7-19, 7-21
 grade crossing safety 2-42
 impatience threshold
 3-11, 3-39, 3-40, 3-41, 3-42

pedestrian (<i>continued</i>)	
level of service	3-30, 7-1, 7-7, 7-8, 7-11, 7-13, 7-21, 7-29, 7-31, 7-33
linkages to transit	2-2
multi-activity areas	7-15, 7-16, 7-19, 7-20
queuing	7-21
signals	3-11
space	7-7, 7-8, 7-9, 7-12, 7-14, 7-28, 7-36
speed	3-10, 3-41, 7-7, 7-8, 7-9, 7-12, 7-21
start-up time	3-41
time-space	7-8, 7-15, 7-16
two-stage street crossing	3-41
volumes, effect on capacity	4-48, 4-51
walkways	7-8, 7-29
people-movers	5-91
<i>see also</i> automated guideway transit	
percent person-minutes served	
<i>see</i> Transit Level of Service Indicator, Florida	
performance measurement, transit	
availability	1-7, 3-2, 3-3
capacity	3-5
categories of measures	3-2, 3-3, 3-26, 3-29
comfort and convenience	3-2
community impacts	1-7, 3-3
defined	3-1, 3-2
economic	3-5
maintenance and construction	1-7, 1-8, 3-5
NTD	3-5
points of view	1-7, 3-5, 3-29
safety and security	1-7, 1-8, 3-5
service monitoring	1-7, 1-8, 3-3
travel time	1-7, 1-8, 3-3
performance, train	
acceleration and braking, effect on comfort	
.....	3-21
AGT	5-55, 5-91
capacity estimation, planning procedure	5-49
effect on minimum headway	5-3, 5-11, 5-14, 5-18, 5-31, 5-62, 5-64, 5-81, 5-91
hybrid-electric bus	2-11
power-to-weight ratio	5-81
uniformity	5-31
person capacity	
<i>see also</i> capacity	
busway	4-45
calculation	5-9, 5-69, 5-70, 5-79
commuter rail	5-88
defined	1-14, 1-16, 4-3, 5-5
factors	1-16, 1-17, 4-16, 4-17, 4-41, 5-7
frequency, effect of	1-10, 4-17, 4-18
HOV lane	4-45
maximum load section	4-16, 4-17
maximum North American	1-20, 1-21
maximum schedule load	4-17, 4-18
mixed traffic	4-58
peak hour factor	4-17
planning applications, rail	5-51, 5-54
planning applications, ropeway	5-55
relation to vehicle capacity	4-50
ropeway	5-97
theoretical	1-17
trip length, effect of	4-17
ways to improve	4-41, 4-42
person delay	
consideration of	4-20
Philadelphia, PA	
bus	2-5, 2-12
center platform	7-26
commuter rail	
.....	2-24, 2-25, 2-26, 5-8, 5-69, 5-81, 5-84, 5-89
ferry	2-40
heavy rail	2-20, 5-17, 5-25, 5-35
high-speed rail	2-19
light rail	2-2, 2-24, 5-8, 5-69
passenger load standards	5-25
ridership	2-2
skip-stop operations	5-35
streetcar	2-22, 2-23
Phoenix, AZ	3-13
Pittsburgh, PA	
AGT	2-29
BRT	2-16
bus	2-13
busway	2-8, 4-21
fare collection	5-37
flat junction	5-4
inclined plane	2-30, 2-31, 2-32, 5-45
light rail	2-23, 5-9, 5-39
streetcar	2-23
planning applications	
AGT	5-55
rail	5-49, 5-50, 5-51, 5-54, 5-55
ropeway	5-55, 5-56
platform, station	
accessibility	7-17, 7-26
center	5-3, 5-15, 7-26
circulation	7-17, 7-18, 7-19
dead areas	7-27
design factors	5-45, 7-8, 7-17, 7-26, 7-27
dual-faced	5-17
elements	7-27
emergencies	
.....	7-17, 7-18, 7-30, 7-32, 7-34, 7-36, 7-41
entrance and exit locations	5-6
far-side	5-77
height	5-38, 5-39, 5-41, 5-42, 5-44, 7-4
length	5-7, 7-27
level of service	7-26
mini-high	5-37, 5-38, 5-41, 5-42, 5-44
multiple	5-35, 5-93
passenger distribution	5-6, 5-37, 7-27
profiled	5-42
queuing area	7-26, 7-27, 7-28
side	5-15, 7-26
signage	7-44
sizing	7-27, 7-28
wheelchair loading	5-41, 5-42, 5-43, 5-44
width	5-16, 5-37, 7-27, 7-28
platooning	4-14, 4-33
Port Aransas, TX	6-4
Portland, ME	2-40
Portland, OR	
bus	2-10, 2-12, 2-13, 4-7
bus lane	2-9, 4-25
bus mall	2-13, 4-24, 4-32
elevator	7-39
fare collection	5-37
lifts, platform-mounted	5-43
light rail	2-2, 2-22, 2-23, 2-24, 5-8, 5-9, 5-24, 5-40, 5-69, 5-76

Portland, OR (*continued*)

- low-floor cars.....5-40
- side platform7-26
- signal priority 2-15, 4-27
- stairway7-32
- streetcar2-23, 5-37, 5-40, 5-74
- yield-to-bus.....4-30

Porto Alegre, Brazil.....4-22

power

- commuter rail 2-25, 5-81
- ferry.....6-4
- heavy rail.....2-18
- light rail 2-21, 5-9

power-to-weight ratio..... 5-81, 5-87

Prague, Czech Republic.....2-30

predictive control

- automatic train supervision5-14

pre-emption, signal 4-25, 5-54, 5-57, 5-75, 5-76

priority

- see* transit priority

progression, signal5-75

proof-of-payment 2-16, 4-5, 4-42, 7-4, 7-43

Providence, RI..... 2-40, 4-22

public address systems.....7-45

públicos 2-4, 2-7

Q

quality of service

- see* **Part 3**

- accessibility, effect of.....3-11
- amenities, effect of.....3-21
- appearance of transit, effect of.....7-45
- appearance, transit3-21
- availability 3-6, 3-27
- capacity, effect of 1-10, 3-16
- cleanliness, effect of..... 3-26, 3-27
- comfort and convenience
.....3-6, 3-7, 3-8, 3-21, 3-26, 3-27, 5-27, 5-67
- cost, effect of 3-21, 3-27
- courtesy, effect of.....3-27
- customer satisfaction survey 3-24, 3-25
- defined 1-7, 3-1, 3-5
- demand-responsive 3-3, 3-53, 3-54
- factors3-26
- fare collection, effect of1-10
- fixed-route..... 3-2, 3-3
- frameworks.....1-9, 3-2, 3-3, 3-26, 3-29, 3-53
- frequency, effect of 1-10, 1-11
- impact score 3-24, 3-25
- index3-23
- information, effect of 3-17, 3-26, 3-27
- level of service 3-22, 3-23
- low-floor buses, effect of1-10
- maintenance, effect of3-8
- measures..... 1-9, 3-29
- nuisances, effect of.....3-26
- on-time performance, effect of3-27
- passenger environment survey 3-25, 3-26
- passenger loads 3-18, 5-26, 5-27, 5-29, 5-30
- perceptions of time3-20
- points of view 3-5, 3-29
- priority measures, effect of1-10
- quadrant analysis.....3-25

quality of service (*continued*)

- reliability, effect of 3-18
- report card1-9, 3-3, 3-29
- ridership, effect on 1-11
- safety and security, effect of
..... 3-8, 3-20, 3-26, 3-27
- scheduling, effect of3-16, 3-26, 3-27
- service area, size of 3-27
- service coverage, effect of 3-9
- service delivery 3-7
- service denials..... 3-16
- speed, relationship to 1-10
- stop spacing, effect of 1-10
- street pattern, effect of 3-11
- transfers, effect of3-20, 3-26, 3-27
- transit priority, effect of 4-19
- travel time, effect of3-19, 3-27, 3-58
- trips not served, effect of.....3-57, 3-58

Québec, QC2-32, 2-34

Queenstown, NZ..... 2-33

queue bypass 2-9, 4-23, 4-24, 4-27

- see also* transit priority

queue jump 2-9, 4-20, 4-27, 4-28

- see also* transit priority

queuing areas

- emergencies7-34
- escalator7-35, 7-36
- level of service7-8, 7-14, 7-15, 7-26, 7-28
- moving walkway7-38
- platform7-26, 7-27, 7-28
- stairways..... 7-34

Quito, Ecuador 4-22, 7-4

R

rail

- see also* individual modes

- capacity **Part 5**
- description..... 2-17
- fare collection 5-22
- line length by mode 2-17
- passenger loads
..... 5-25, 5-26, 5-27, 5-28, 5-29, 5-30
- passenger service times.....5-19, 5-22
- peak hour factors, selected systems 5-8
- ridership, annual by mode 2-17
- ridership, annual North America 2-17
- ridership, grade-separated 5-57
- right-of-way types..... 2-18
- speed by mode..... 2-17
- station elements 2-42
- station spacing by mode 2-17
- wheelchair access
.. 5-37, 5-38, 5-39, 5-40, 5-41, 5-42, 5-43, 5-44

railroads, freight

- commuter rail, negotiations with 2-24, 5-82

ramps7-40, 7-41

re-entry delay 4-7

reference speed..... 5-12

regional rail

- see* commuter rail

reliability

- as quality of service factor 3-7, 3-18, 3-45, 3-56
- demand-responsive service 3-56, 3-57

reliability (<i>continued</i>)	
distance between mechanical breakdowns	3-45
factors	3-19
headway adherence	3-45, 3-47, 3-48
influence of failure rate	4-8
measures	3-56
missed trips	3-45
on-time performance	3-45, 3-46, 3-47, 3-56
passenger loads, effect of	3-43
transit priority, effect of	4-19
travel time	3-58
trips not served	3-57
wheelchair lifts	5-38, 5-42, 5-43
Reno, NV	2-29
reserved lanes, bus	4-24
reserved lanes, light rail	5-71, 5-75
response time	3-53, 3-54
retail sales at stops and stations	7-5
reverse commute	5-83
ride comfort	3-21
riders, captive	2-1
riders, choice	2-1, 3-13, 3-29
ridership	
annual U.S. by mode	2-4
bus, top systems	2-5
demand-responsive	4-61, 4-63
estimating	1-11
fare, effect of	1-12
frequency, effect of	1-11
quality of service, effect of	1-11
rail, annual by mode	2-17
rail, annual North America	2-17
rail, grade-separated	5-57
reliability, effect of	1-12
service area, effect of	1-12
right turns	
adjustment factor	4-49, 4-51, 4-58
effect on capacity	4-48, 4-49, 4-51, 4-52
prohibiting	4-47, 4-49, 4-52
right-of-way	
exclusive	2-18
rail, general	2-18
segregated	2-18
shared	2-18
ropeways	
bicable system	2-32
cabin size	2-32, 5-97
capacity, North American systems	2-34
carrier spacing	2-33, 5-96
continuously circulating system	2-32, 5-55, 5-96
described	2-32, 2-33, 5-95
dwell time	5-95, 5-96
funitels	2-33
grips	5-95
illustrated	2-33
monocable system	2-32
number of agencies, U.S.	2-3
passenger loading	2-32, 2-33, 5-95
peak hour factor	5-97
person capacity	5-97
pulse system	2-33
reversible system	2-32, 5-55, 5-95, 5-96
ridership, annual U.S.	2-4
ropeways (<i>continued</i>)	
speed	2-32, 5-95
stations	2-33, 5-95
types	2-32, 5-95
rural bus service	2-7
rural ferry service	2-38
rural service	4-61
S	
Sacramento, CA	
light rail	2-2, 2-23, 2-24, 5-8, 5-41, 5-73
park-and-ride	3-13
safety and security	
as quality of service factor	3-8, 3-20
crashes	5-16
factors	3-20
lighting, effect on	7-45
loading areas	7-25
stations	7-18
Salt Lake City, UT	2-23, 5-41
San Antonio, TX	2-10
San Diego, CA	
bi-level rail car	2-26
car-mounted lift	5-43
commuter rail	2-26, 5-44
ferry	2-40
HOV lane	4-21
light rail	2-2, 2-22, 2-23, 5-24, 5-42, 5-47, 5-75, 5-77
station amenities	7-46
trolley	5-8, 5-9
San Francisco, CA	
boarding island	4-29
bus	2-5, 2-13
bus lane	2-10, 4-25
cable car	2-35, 5-95
commuter rail	2-26, 5-8, 5-44, 5-89
farecards	7-41
ferry	2-37, 2-40, 6-1, 6-2, 6-4, 6-7, 6-8, 6-12
heavy rail	2-19, 2-20, 5-19, 5-20, 5-24, 5-25, 5-32, 5-33, 5-66
light rail	2-2, 2-23, 5-24, 5-39, 5-41, 5-51, 5-66, 5-79
passenger load standards	5-25
streetcar	2-22
ticket machines	7-43
Transbay Terminal	7-24
San Jose, CA	
bicycle lockers	3-13
commuter rail	2-26
light rail	2-23, 5-43
San Juan, PR	
ferry	2-40
heavy rail	2-20
São Paulo, Brazil	4-22
sawtooth loading areas	4-12, 7-24, 7-25
schedule recovery time	5-16, 5-31, 5-38
scheduling	
<i>see</i> headway and hours of service	
school buses	2-2
security	
<i>see</i> safety and security	
seating configurations	5-27, 5-29, 5-88

Seattle, WA	
bi-level rail car.....	2-26
BRT.....	2-16
bus tunnel.....	2-14
busway.....	2-8, 4-21, 4-22, 4-45
commuter rail.....	2-26
ferry.....	2-37, 2-39, 2-40, 6-1, 6-2, 6-3, 6-4
HOV lane.....	4-21
monorail.....	2-29, 2-30
park-and-ride.....	3-13, 3-15, 3-16
vintage trolley.....	2-23, 5-73
Seattle-Tacoma Airport.....	2-29, 5-92
segregated right-of-way.....	2-8
service coverage	
accessibility.....	3-11
as quality of service factor.....	3-32, 3-37
bicycles, effect of.....	3-11, 3-12
calculated.....	3-33, 3-34, 3-35, 3-36, 3-37
coverage area.....	3-33, 3-37
defined.....	3-9
examples.....	3-34, 3-35, 3-36
grade factor.....	3-39
levels of service.....	3-32, 3-33, 3-34
Local Index of Transit Availability.....	3-42
measures.....	3-32
network connectivity index.....	3-39
park-and-ride lots, effect of.....	3-37, 3-43
pedestrian crossing factor.....	3-39, 3-40
pedestrian environment.....	3-10
percent jobs served.....	3-42
percent people served.....	3-42
percent person-minutes served.....	3-42
population factor.....	3-39
street connectivity factor.....	3-38, 3-39
street pattern, effect of.....	3-11, 3-38
Transit Service Accessibility Index.....	3-42
transit-supportive area.....	3-33
walking distance.....	3-9, 3-10
service delivery	
comfort.....	3-7
customer service.....	3-7
defined.....	3-7
goal accomplishment.....	3-7
reliability.....	3-7
service denials.....	3-16
service measure.....	3-2, 3-3, 3-27, 3-29, 3-53
service span	
<i>see</i> hours of service	
service times, passenger	
<i>see</i> passenger service times	
shared bus lanes	
<i>see</i> HOV lanes	
shared right-of-way.....	2-18
shelters.....	7-28
Shirley Highway, Virginia.....	2-9, 2-13
short turns.....	5-46, 5-58
sidings.....	5-86, 5-87
Sidney, BC.....	6-5
signal priority.....	2-14, 2-15, 4-25, 4-38, 4-39
active.....	4-25, 4-26
conditional.....	3-19, 4-25, 4-26
described.....	4-25
guidelines for implementation.....	4-26
illustrated.....	4-26
passive.....	4-25, 4-26
signal priority (<i>continued</i>)	
performance measures.....	4-27
pre-emption.....	4-25, 4-26
real-time.....	4-25, 4-26
treatments.....	4-26
unconditional.....	4-25
signals, train	
automatic train control.....	5-11, 5-13
blocks	
.....	5-2, 5-11, 5-12, 5-78, 5-79, 5-83, 5-85, 5-86
cab.....	5-12
effect on minimum headway	
.....	5-4, 5-13, 5-18, 5-51, 5-57, 5-71, 5-79
fixed-block.....	5-11, 5-12, 5-13, 5-51, 5-60, 5-63
functions.....	5-11
hybrid.....	5-13
moving-block.....	5-12, 5-13
railroad.....	5-83
signal aspects.....	5-2, 5-11
throughput.....	5-11, 5-14
types.....	5-11
simulation, use of	
bus capacity estimation.....	4-14
bus clearance time.....	4-7
close-in time.....	5-14
pedestrian circulation.....	7-16
rail capacity estimation.....	5-55, 5-62, 5-81, 5-85
single-track operation	
.....	5-46, 5-53, 5-57, 5-71, 5-72, 5-73, 5-78, 5-83
skip-stop operation	
adjustment factor, capacity	
.....	4-49, 4-50, 4-51, 4-54
adjustment factor, speed.....	4-54
effect on capacity	
.....	4-3, 4-32, 4-33, 4-49, 4-50, 4-51, 5-35
effect on dwell time.....	4-5
effect on speed.....	4-32, 4-33, 4-52, 4-53, 4-54, 5-35
slack time.....	5-3
Small Waterplane Area Twin Hull vessels.....	6-3
space, pedestrian.....	6-15, 7-7, 7-8, 7-9,
.....	7-12, 7-13, 7-14, 7-23, 7-26, 7-28, 7-36
spacing, stop or station	
design standards.....	4-33
effect on speed.....	4-46, 4-52, 4-59
effect on travel time.....	4-53
special events.....	5-47
speed	
AGT.....	5-91, 5-121
base bus.....	4-46, 4-52, 4-53, 4-54, 4-59
bicycles.....	3-12
bus lane.....	4-52, 4-53, 4-54
busway.....	4-46
default value, simple procedure.....	5-50
effect on train stopping distance.....	5-64
escalator.....	7-35
ferry.....	6-2, 6-3, 6-4
HOV lane.....	4-46
limits, curves and switches.....	5-11, 5-60
moving walkways.....	7-37
North American modes.....	1-21
pedestrian.....	3-10, 3-41, 6-15, 7-7, 7-8, 7-9, 7-12
reference.....	5-12
station approach.....	5-16, 5-60, 5-63, 5-64
stop spacing, effect of.....	1-10
ways to improve.....	4-41, 4-42

Squaw Valley, CA.....	2-33, 2-34	taxis	
St. Louis, MO.....	2-23, 5-38	market.....	2-2
stairways		water taxi.....	6-2
capacity.....	7-12, 7-13, 7-33, 7-34	TDM	
conflicts.....	7-12, 7-33	<i>see</i> transportation demand management	
design factors.....	7-33	telephones.....	7-45
emergency use.....	7-18	Telluride, CO.....	2-33, 2-34
illustrated.....	7-32	terminals	
level of service.....	7-13, 7-14	accessibility.....	2-41, 3-37, 7-16, 7-17
pedestrian flow rates.....	5-36, 7-12, 7-13, 7-33	as rail capacity constraint.....	5-3
pedestrian speeds.....	7-12	berth productivity.....	2-14, 7-25
queuing.....	7-13, 7-33	capacity.....	Part 7
queuing area.....	7-34	circulation.....	7-17, 7-19
sizing.....	7-8, 7-12, 7-33, 7-34	dead areas.....	7-27
supplement to escalators.....	7-33	design.....	2-14, 2-41, 5-15, 5-16, 5-77, 7-17, 7-28
width, effect on capacity.....	7-12, 7-33	doorways.....	7-31
standard bus		elements.....	2-41, 7-1
<i>see</i> bus, standard		elevators.....	7-38, 7-40
standing area, rail.....	5-27	emergencies	
station spacing		7-17, 7-18, 7-30, 7-32, 7-34, 7-36, 7-41
<i>see</i> spacing, stop or station		escalators.....	7-33, 7-34, 7-36
stations		fare gates.....	7-41, 7-42
<i>see also</i> terminals		ferry.....	6-4, 6-5, 6-6, 6-7, 6-10, 6-12, 6-13, 6-17
commuter rail.....	5-44	information displays.....	7-44, 7-45
light rail.....	5-38, 5-71, 5-72, 5-75, 5-76, 5-77	intermodal.....	2-42, 3-14, 7-5
ropeway.....	5-45	layover.....	5-15, 5-16, 5-17, 5-34
stations, busway.....	7-4	loops.....	5-17
stations, commuter rail.....	7-4	micro-peaking.....	2-41
stations, heavy rail.....	7-4	moving walkways.....	7-37
stations, light rail.....	7-4	public address systems.....	7-45
stops		ramps.....	7-40
<i>see</i> bus stops <i>and</i> off-line stops		seating.....	7-28
street pattern, as quality of service factor.....	3-11	security.....	7-18
streetcar		shelters.....	7-28
<i>see also</i> light rail		signage.....	7-44
capacity.....	5-54, 5-74, 5-75	speed restrictions.....	5-16
coefficient of variation, dwell times.....	5-76	stairways.....	7-32, 7-33
low-floor cars.....	5-40	systems perspective.....	7-1
right-of-way types.....	2-18, 5-54, 5-74, 5-75	ticket machines.....	7-44
terminals.....	5-16, 5-17	train storage.....	5-46, 5-47, 5-84
train signals.....	5-2	transit centers.....	2-42
supply, influence on capacity.....	5-7	transit stations.....	2-42
Surface Effect Ships.....	6-3	waiting rooms.....	7-28
surveys, customer satisfaction.....	3-24, 3-25, 3-45	walkways.....	7-8, 7-9, 7-10
surveys, passenger environment.....	3-25, 3-26, 3-45	wayfinding.....	7-18
switch number.....	5-86	three-aspect signal systems	
switches, effect on minimum headway		<i>see</i> fixed-block signal systems	
.....	5-4, 5-17, 5-72, 5-93	throughput, train	
Sydney, Australia		cab signals.....	5-63
catamaran.....	6-3	commuter rail.....	5-81, 5-83
ferry.....	2-37, 2-39, 6-5, 6-7	factors.....	5-14, 5-75
monorail.....	2-30	fixed-block.....	5-11, 5-12, 5-63
Syracuse, NY.....	2-26	junctions.....	5-14, 5-17, 5-57, 5-83
		light rail, on-street operation.....	5-75
		moving-block.....	5-14, 5-63
		streetcar.....	5-74
		terminals.....	5-14, 5-15
		turnbacks.....	5-57, 5-58
		ticket machines	
		number of.....	7-44
		processing time.....	7-43
		time	
		close-in.....	5-13, 5-14, 5-58, 5-64
		crew turnaround.....	5-15, 5-58
		jerk-limiting.....	5-50, 5-59, 5-72, 5-73, 5-91, 5-121

T

Tacoma, WA	
ferry.....	2-40
streetcar.....	2-23, 5-40
Tallahassee, FL.....	2-12
Tampa, FL	
monorail.....	2-29
vintage trolley.....	2-23

time (<i>continued</i>)	transit
passenger service5-19, 5-20, 5-21, 5-22	mode share 2-1
perceptions of3-20	role of2-1
response..... 3-53, 3-54	service configurations..... 2-2
schedule recovery 5-16, 5-31	transit agencies
wait, elevator7-39	by mode, Canada 2-3
wait, queuing area7-14	by mode, U.S..... 2-3
time window 3-56, 3-57	by size, U.S. 2-3
tokens 6-12, 7-42	transit centers
Tokyo, Japan.....5-23	amenities..... 2-42
Toronto, ON	described.....2-42, 4-12, 7-3
AGT technology2-27	design 2-42
bi-level rail car.....2-26	design factors 7-24
bus 2-5, 2-14	illustrated..... 2-41
commuter rail2-24, 2-26, 2-27,	Transit Level of Service Indicator, Florida... 3-42
.....5-8, 5-44, 5-68, 5-84, 5-89, 5-120	transit line capacity
heavy rail..... 2-19, 2-20, 5-8, 5-19, 5-24,	<i>see</i> person capacity
..... 5-25, 5-32, 5-33, 5-66, 5-68, 5-69, 5-120	transit mall
light rail 2-2, 2-24	<i>see also</i> bus lanes, bus malls
loading diversity5-6	light rail..... 5-9
passenger load standards5-25	transit priority
ridership2-2	advance green 4-27
streetcar 2-23, 5-16, 5-74	boarding islands 4-28, 4-38, 4-39
track circuits5-12	bus 2-14, 2-15, 4-19, 4-20
track separation	bus lanes 4-24, 4-37
effect on headway 5-16, 5-18	bus stop consolidation 4-32
tracks, multiple5-85	bus stop relocation 4-31
traffic	busways 2-9, 4-20, 4-22, 7-4
influence on capacity..... 4-7, 4-16	capacity, influence on 2-14
traffic signal timing	comparison of treatments 4-34
influence on bus capacity4-10	congestion, influence on 2-1
influence on light rail capacity 5-75, 5-78	curb extensions 4-29, 4-38, 4-39
train control, automatic5-11, 5-13, 5-19	described.....4-19, 4-20
train length2-25, 5-7, 5-8, 5-11, 5-14, 5-18,	design standards 4-33
..... 5-25, 5-29, 5-49, 5-50, 5-59, 5-69, 5-70,	HOV lanes 4-20
..... 5-71, 5-72, 5-75, 5-79, 5-83, 5-88, 5-91	keys to success2-15, 4-19, 4-20
train performance	parking restrictions4-31, 4-38, 4-39
<i>see</i> performance, train	person delay considerations4-20, 4-38
train separation	planning guidelines
minimum, calculating5-59, 5-61, 5-63, 5-64 4-35, 4-36, 4-37, 4-38, 4-39, 4-42
relationship to train length.....5-59	platooning 4-33
train signals	quality of service, influence on 1-10, 2-14
<i>see</i> signals, train	queue bypass.....4-23, 4-27
tramway, aerial	queue jump 4-20, 4-27, 4-38, 4-39
<i>see also</i> ropeways	recovery time, effect on 2-15
applications.....5-95	reliability, influence on 2-14, 4-19
capacity5-55, 5-95, 5-97	ridership, influence on 2-1
low-floor cars.....5-40	right-turn lane exemption..... 4-27
number of agencies, U.S. 2-3	signal 4-25, 4-26, 4-38, 4-39,
ridership, annual U.S. 2-4 5-54, 5-57, 5-73, 5-75, 5-76, 5-78
speeds5-95	travel time, influence on
wheelchair access5-452-1, 2-14, 4-19, 4-23, 4-38
transfers	turn restrictions 4-31
as quality of service factor3-20	uses 4-19, 4-34
commuter rail5-84	yield-to-bus laws 4-30
dwell time, effect on2-14	Transit Service Accessibility Index 3-42
ferry 2-38, 6-1	transit-auto travel time
influence on demand5-36	<i>see</i> travel time, transit-auto
timed5-35	transit-supportive area.....3-33, 3-35, 3-36
train loading, effect on5-6	transportation demand management 3-21
transfer penalty3-20	transportation planning model
travel time, effect on3-20	<i>see</i> model, transportation planning
with rail skip-stop operations.....5-35	transportation system management 2-14
	travel speed, as quality of service factor
1-10, 3-5, 3-49

travel time
 as quality of service factor 3-8, 3-19, 3-49, 3-58, 3-59
 defined 3-58
 demand-responsive service 3-58, 4-63
 factors 3-19, 3-49, 3-59, 4-11
 ferry 2-38, 6-1, 6-3, 6-7, 6-10
 off-line stops, effect of 4-11
 passenger loads, effect of 3-43
 rail skip-stop operation, effect of 5-35
 transit priority, effect of 4-19
 transit-auto
 2-1, 3-19, 3-20, 3-49, 3-50, 3-51, 3-59
 trip lengths, by mode 2-4
 trips not served
 as quality of service factor 3-57, 3-58
 defined 3-57, 3-58
 demand-responsive service 3-57, 3-58
 levels of service 3-58
 missed trips 3-57, 3-58
 reliability 3-57, 3-58
 trips denied 3-57, 3-58
 Tri-Rail 2-22
 trolley, vintage 2-22, 5-38, 5-42, 5-73, 5-75
 trolleybus
 number of agencies 2-3, 2-11
 ridership, annual U.S. 2-4
 TSM
 see transportation system management
 turnbacks 5-57, 5-58
 effect on minimum headway
 5-4, 5-14, 5-15, 5-17
 throughput 5-14, 5-15, 5-17
 two-aspect signal systems
 see fixed-block signal systems

U

unlinked trips 2-3

V

Vancouver, BC
 aerial tramway 2-34
 AGT technology 2-27
 automatic train operation 5-13
 bi-level rail car 2-26
 BRT 2-16
 bus 2-5, 2-13
 bus mall 2-9, 4-24
 busway 2-8, 2-9, 4-22
 commuter rail 2-26, 5-44
 ferry 2-37, 2-40, 6-1, 6-18
 heavy rail 2-19, 2-20, 5-8, 5-22, 5-24,
 5-32, 5-33, 5-58, 5-66, 5-68, 5-69, 5-120
 loading diversity 5-6
 vanpool
 described 2-7
 number of agencies, U.S. 2-3
 ridership, annual U.S. 2-4
 Vashon Island, WA 6-5
 vehicle capacity
 bus effects on passenger vehicles
 4-57, 4-97, 4-98

vehicle capacity (*continued*)
 defined 1-14, 1-17
 factors 1-17, 1-18, 4-11, 4-12, 4-17
 maximum load section 4-17
 relation to person capacity 4-50
 theoretical 1-17
 vehicle equivalence 4-57
 vehicle types
 bus 2-11, 4-18
 commuter rail 5-85
 demand-responsive 4-62
 vending facilities 7-45
 Victoria, BC 2-11, 2-12
 Virginia Railway Express 2-26, 5-8, 5-89
 voltage drops
 default value, simple procedure 5-50
 effect on headway 5-62, 5-63, 5-64
 volume-to-capacity ratio
 walkway 7-10

W

wait time
 demand-responsive service 4-62
 waiting areas
 design factors 7-28
 ferry 6-12, 6-14
 level of service 7-14, 7-15, 7-23, 7-25, 7-29
 seating 7-28, 7-29
 sizing 7-23, 7-28
 waiting rooms 7-28
 walking distance 3-9, 3-33, 3-37
 walking speed 3-10, 3-41
 walkways
 analysis time period 7-29
 capacity 6-15, 7-8, 7-9, 7-29, 7-30
 conflicts 7-9
 design factors 7-9, 7-29
 doorways 7-31
 effective width 7-8, 7-9, 7-10, 7-30
 fare gates, effect of 7-41
 ferry 6-7, 6-10, 6-12, 6-14, 6-15
 level of service 7-10, 7-11, 7-30
 micro-peaking 7-29
 sizing 7-30, 7-34
 stairways 7-33
 volume-to-capacity ratio 7-10
 Washington State Ferries 2-37, 6-4, 6-6
 Washington, DC
 AGT 2-29
 bus 2-5
 commuter rail 2-26, 5-8, 5-89
 farecards 7-41
 heavy rail 2-20, 5-8
 passenger load standards 5-25
 water taxi 2-38, 6-1
 weak link, capacity 5-57, 5-58, 5-71
 Wheatland, OR 2-39
 wheelchairs
 see also Americans with Disabilities Act
 accessibility 2-11, 5-38, 5-45
 dwell time required 4-4, 4-6, 5-37, 5-42, 5-43
 elevators 7-39
 lift reliability 5-42

wheelchairs (*continued*)

- rail platforms
 - 5-37, 5-38, 5-39, 5-41, 5-42, 5-43, 5-44
- space requirements.....5-38
- width
 - effective, bus stop7-23
 - escalator.....7-35
 - stairway 7-12, 7-13, 7-33
 - walkway7-8, 7-9, 7-10, 7-30
- Wuppertal, Germany 2-29, 2-30

XYZ

- yield-to-bus laws 4-7, 4-30
- Zürich, Switzerland.....2-30

This page is intentionally blank.