

HIGHWAY RESEARCH BOARD
Special Report 87S

SUBJECT
INDEX
TO
HIGHWAY
CAPACITY
MANUAL
1965

National Academy of Sciences
National Research Council
Publication 1328

HIGHWAY DEPT. LIBRARY

SUBJECT INDEX

- AADT**
 - (see Annual average daily traffic)
- AADT/hourly volumes**
 - (see Hourly volumes/AADT)
- Access control**
 - definition, 8
 - without access control, 280-337
 - (see specific roadway type)
- Adjustment factors**
 - (see Factors affecting capacity and service volume)
- Alinement**
 - definition, 93
 - effect of restrictions, 94, 262, 291, 301, 308
 - effect on capacity, multilane rural highways, 291
 - effect on speed, 95
- Annual average daily traffic (AADT)**
 - definition, 16
 - related to hourly volumes, 36-42
- Areas, types of**
 - definitions, 19
- Arterials**
 - (see Urban and suburban arterials)
- At-grade intersections**
 - (see Intersections at grade)
- Auxiliary lanes**
 - definition, 10
 - (see Roadway factors affecting capacity)
- Average overall travel speed, 319, 323**

- Basic capacity, 2**
- Bottlenecks**
 - break points, 67
 - breakdown conditions, 330
 - congestion index, 56
 - critical density, 60, 62
 - critical vs maximum density, 68
 - definition, 19
 - forced flow, 250-251
 - unstable flow, 250
 - (see also Spacing and headway characteristics)
- Bridges and tunnels**
 - bus volume, 342
 - maximum observed volumes, one-way, 27-28
 - maximum observed volumes, two-way, 23-27
- Bus**
 - definition, 15
- Bus lanes**
 - effect on capacity, 340, 345
- Bus operations**
 - acceptable headways, 347
 - intersection effects, 143-145
- Bus stops, 346**
 - effects on capacity, 124-125
 - far-side bus stop, 124, 142, 144-145
 - mid-block bus stop, 125
 - mid-street bus platform, 125
 - near-side bus stop, 124, 142-144
 - freeway, 348
 - loading and unloading time, 344
 - minimum length, curb loading zones, 348
- Bus transit**
 - characteristics, 338
 - effects on capacity, 340
 - equivalency factors, 345
 - intersection capacity, 129, 345
 - peak-hour volumes, 340-342
 - reserved transit lanes, 340, 345
 - transit in CBD, 338
 - uninterrupted flow headways, 342-343
- Buses**
 - adjustment factors, 143, 260
 - adjustment factors, multilane, 290
 - adjustment factors, two-lane, 307
 - passenger car-bus equivalent, 260, 306
 - passenger car/bus equivalent, multilane, 289
 - passenger car/truck/bus equivalent, 287
 - passenger car/truck/bus equivalent, two-lane, 304, 306
 - effect on capacity, 142
 - loading zone length, 348
 - on and off time, 346
 - peak-hour volumes, 340-342
 - signalized intersections, 124-125
 - speed on sustained grade, 104

- Capacity**
 - basic, 2
 - bus transit, effect on, 340
 - definitions, 5-22
 - index to, 20-21
 - freeways and expressways with "ideal" geometrics, 246
 - ideal, 2
 - intersection, predicted vs actual, 112
 - lane markings, effect on, 128
 - limiting measures, 5-6
 - multilane rural highway, 294
 - physical characteristics, effects of, 113
 - possible, 2, 5, 87
 - practical, 2, 87
 - prevailing conditions, 6
 - signalized intersections, typical examples, 146-155
 - time period, 2
 - three-lane highway, 318

- travel desires, 2
- two-lane highway, 299, 309
- typical conditions, 3
- urban and suburban arterials, 320-333
(see Intersection capacity, Levels of service, Ramps, Weaving sections)
- Capacity and level of service
 - capacity for interrupted flow, 77-78
 - capacity for uninterrupted flow, 75-77
 - freeways and expressways, 245-251
 - intersections, 129-131
 - level of service determination, 81
 - levels of service, 2, 78-80
 - operating conditions for levels of service, 80
 - ramps, 191-197
 - streets and highways, 283, 300, 318
 - summary of procedures, 81-87
 - weaving sections, 163-176
(see also Levels of service)
- Capacity and service volume factors, 88-110
(see also Roadway factors affecting capacity and Traffic factors)
- Capacity for interrupted flow, 77-78
(see also specific roadway type)
- Capacity for uninterrupted flow, 75-77
(see also specific roadway type)
- Capacity Manual, 1950, vii, 2
- Capacity-speed relationships
(see specific roadway types)
- Chapter references
(see References, chapter)
- Characteristics of roadway facilities
 - downtown streets, 332
 - freeways and expressways, 245
 - intersections at grade, 111
 - ramps, 187
 - streets and highways, 280
 - urban and suburban streets, 318
 - weaving sections, 160
(see also Traffic characteristics)
- Climbing lanes, 93, 110, 259
definition, 10
- Cloverleaf interchanges
effect on capacity, multilane rural highways, 289
- Commercial vehicles
(see Buses and Trucks)
- Composition of traffic
(see Traffic composition)
- Computational procedures
 - auxiliary lanes, ramps, 202, 222
 - auxiliary lanes, weaving, 167
 - basic freeway sections, 263-265
 - capacity determination, 265-266
 - design hours, 37-38
 - evaluation of composite freeways, 267-270
 - freeways, expressways, 263-270
 - examples, typical solutions, 270-279
 - intersection capacity, 131-146
 - Normann method, 112
 - multilane rural highways, 293-294
 - observed and computed values, 133
 - ramps, 225-226, 234-236, 242-243
 - service volume, 198-221, 265-266
 - streets and highways, 293, 309, 327, 334-337
 - subsection analysis, expressways, 263
 - two-lane highways, 309-314
 - urban and suburban arterials, 327-332
 - weaving sections, 182, 186
 - weighted levels of service, 268-270
(see also specific roadway type)
- Conditions affecting capacity
(see Factors affecting capacity and service volume and Environmental conditions)
- Control devices
 - definitions, 14-15
(see also Intersections at grade)
- Control measures, 126-129
- Control of access
(see Access control)
- Controls
(see Turn controls and Signals)
- Critical density, 71-73
definition, 17
- Critical elements
 - freeways and expressways, 255-262
 - multilane rural highways, 283-292
 - two-lane roads, 301-308
 - type of highways, 73
 - urban and suburban arterials, 324-326
- Critical points
 - effect on level of service, 247
 - freeways and expressways, 247
 - obstructions, 89
 - point restriction, 89
 - ramps, 197
(see also specific roadway type)
- Curves
(see Alinement, Vertical curves)
- Cycle length
(see Signals)
- Daily speed variations, 45-46
- Definitions, 4-21
index, 20-21
(see also specific subject)
- Density
(see Speed, flow and density relationships)
- Design
(see specific element)
- Design hour and hourly volume, 16, 36-44
- Determination of level of service
(see Capacity and level of service)
- Diamond interchanges
effect on capacity, multilane rural highways, 291, 308

- Direct connection interchange
 - effect on capacity, multilane rural highways, 289
- Directional distribution, 29
- Downtown streets
 - characteristics, 332
 - "breakdown" condition, 333
 - examples, typical solutions, 334-337
 - general considerations, 332
 - levels of service, 333-334
 - limitations to analysis, 332
 - (see also Streets and highways)
- Driver characteristics
 - effect on ramp operation, 189
- Effects of grades, 95-110, 255, 260, 306
 - (see also specific highway type)
- Environmental conditions
 - effect on capacity, 7, 115
 - related to signals, 112, 115-122
- Equations, formulas
 - bus adjustment factor, 105
 - capacity, expressway, 265
 - composite distribution, 55
 - density, 51, 58
 - exponential distribution, 54
 - for capacity, multilane rural highway, 294-295
 - freeway capacity and service, 265-266
 - headway, 49
 - highway capacity, multilane, 294-295
 - Poisson distribution, 53
 - ramp analysis, 200-221
 - rate of flow, 59
 - service volume
 - (see specific highway type)
 - signal split ratio, 146, 156
 - speed-volume, 51
 - statistics for, 390-395
 - substitution, ramps, 225
 - two-lane road, 309, 313
 - volume, 51
 - weaving lanes required, 168-169, 181
- Equivalents
 - definition, 19
 - passenger car/bus, 129, 260, 306, 345
 - passenger car/bus, multilane, 289
 - passenger car-bus, two-lane, 306
 - passenger car/trucks, 102, 258
 - passenger car/truck/buses, 257, 287
 - passenger car/truck, multilane, 288
 - passenger car/truck, two-lane, 304-305
 - passenger car/truck by grades, 103
 - passenger car/truck by speeds, 102
 - service volume, passenger car/truck, 103
 - (see also specific roadway and vehicle type)
- Examples (Typical solutions)
 - downtown streets, 334-337
 - freeway and expressway analysis, 270-279
 - multilane rural highways, 298-299
 - ramps, 228-233, 239-242
 - signalized intersection, capacity determination, 146-155
 - two-lane highways, 314-317
 - turning movements, 152-155
 - urban and suburban arterials, 329-332
 - weaving sections, 156, 160-163, 177-186
- Expressways
 - definition, 8
 - (see Freeways and expressways)
- Factors affecting capacity and service volume, 88-100
 - by highway type
 - freeways and expressways, 251-262
 - multilane rural highways, 283-293
 - ramps, 189-191
 - signalized intersections, 112-129
 - streets, downtown, 333
 - three-lane highways, 301-308
 - two-lane highways, 301
 - unsignalized intersections, 155
 - urban and suburban arterials, 324
 - weaving sections, 160-172
 - roadway factors
 - alignment, 93
 - auxiliary lanes, 91-93
 - grades, 95-100
 - lane width, 88
 - lateral clearance, 89, 255
 - lateral clearance and lane width, 90, 255
 - shoulders, 90
 - surface conditions, 93
 - traffic factors
 - at-grade intersections, 168
 - buses, 104
 - lane distribution, 105
 - traffic interruption, 106
 - trucks, 101
 - variations in flow, 106
- Factors affecting flow
 - buses, 255-259
 - by highway type
 - freeways and expressways, 251-262
 - multilane rural highways, 283, 285
 - ramp, 189-191
 - signalized intersections, 112-119
 - streets, 333
 - three-lane roads, 301
 - two-lane roads, 301
 - weaving, 160, 286-289
 - control measures, 126-129
 - free-flow conditions, 249
 - grades, 95-100, 255-259
 - (see also Grades)
 - lane markings, 128
 - lane-width, 89, 255

- lateral clearance, 89, 255
- trucks, 255-259
- flow-density relationships
 - congestion, 71
 - critical density, 71
 - curvilinear relationships, 71
 - directional distribution, 29
 - instantaneous flow, 72
 - kinematic waves, 72
 - queue, 72
- Flow, density, speed relationships
 - (see Speed, flow and density relationships)
- Flow variations
 - daily, 32
 - directional, 39
 - distribution by direction, 29
 - distribution by lane, 29
 - distribution by routes, 25
 - hourly, peaking, 32
 - seasonal, 30
 - uninterrupted, 76, 89
 - weekly, 30
 - (see also Traffic flow and Volume)
- Forced flow, 251
- Formulas
 - (see Equations, formulas)
- Four-way stop
 - intersection capacity, 158-159
- Freeways and expressways
 - balance among elements, 245
 - basic levels of service, 245-251
 - capacity of "ideal" geometrics, 246
 - critical points, effects on levels of service, 247
 - definition, 8
 - geometrics, effects of, 245-247
 - levels of service evaluation, 246-251
 - operating speeds as measure of service, 246
 - v/c ratio as determinant of levels of service, 246
 - characteristics, 245
 - computational procedures
 - basic freeway sections, 263
 - capacity determination, 265-266
 - demand v/c ratio as service index, 264
 - equations, capacity and service volume, 265-266
 - evaluation of the composite freeway, 267-270
 - levels of service, 266
 - operating speed as determinant of service, 264
 - service volume determination, 265-266
 - subsection analysis, 263, 273-277
 - weighted level for composite index, 268-270
 - critical elements
 - adjustment factors, 255-261
 - alignment, 262
 - auxiliary lanes, approach and exit, 262-263
 - buses, 255-259
 - climbing lanes, auxiliary lanes, 259
 - conflict area, 261
 - control of access, 262
 - design features to overcome problems, 261
 - factors affecting flow, 251-255
 - grades, 255-259
 - interruptions, 262
 - lane width, 255
 - lateral clearance, 255
 - merge point as critical point, 262
 - passenger car equivalents, 257-261
 - ramp terminals, 260
 - ribbon development, 262
 - signal spacing, 263
 - signalization, 252-263
 - subsection balance, 252-254
 - trucks, 255-259
 - weaving areas, 260
 - examples
 - capacity and service, 270-279
 - forecasting, hourly volumes, 44
 - level of service A, 247-248
 - free-flow conditions, 248
 - level of service B, 248
 - level of service C, 248
 - rate of flow on expressways, 249
 - v/c relationships, 247-251
 - level of service D, 250
 - bottlenecks, 250
 - conflict points, 250
 - forced flow, 250
 - peak-period conditions, 250
 - unstable operation, 250
 - level of service E, 250
 - forced flow, 250
 - peak-period conditions, 250
 - unstable flow, 250
 - level of service F, 251
 - bottlenecks, 251
 - capacity, 251
 - forced flow, 251
 - jammed conditions, 251
 - levels of service and maximum volumes, 252-253
- Frictions
 - definitions, 18, 19
 - effect of, 308
- Gap acceptance and characteristics
 - (see Spacing and headway characteristics)
- Gap, vehicular
 - definition, 16
- Geometrics
 - alignment, 291
 - combinations, 203
 - conflict areas, 250

- Geometrics** (*continued*)
 effect of, on capacity and level of service, 77, 188, 245-247
 effect of restricted width, 88-89, 256, 286, 288
 lane width, 255-256, 285-286
 point restrictions, 297
 roadway features, 6-7
 sight distance, 301
- Grades**
 definition, 14
 effects of, 95-110
 climbing lanes and passing bays, 100
 grades on freeways, 255, 257-259
 on passenger cars, 95-97
 passenger car equivalents, 99
 truck performance on sustained grades, 97
 up-grade equivalency, 101-102
 vertical curves in grade profile, 97-98
 weight-power ratio on grade performance, 98-99
- Green time/cycle time (*G/C*) ratio**, 133, 138
- Headway**
 acceptable for buses, 347
 as time measure, 49
 at various volumes, rural highways, 52-53
 definition, 16
 distribution downstream from traffic signal, 59
 frequency distribution, by time length, 58
 gap acceptance, 57
 lane distribution, expressway, 54
 mixed traffic, 342-343
 two-lane and four-lane at 500 vph, 55
 two-lane urban street, 56
 (see also Spacing and headway characteristics)
- Highest hour trends**, 43-44
- Highway factors affecting capacity**
 (see Factors affecting capacity and service volume)
- Highways**
 definition, 8
 (see specific roadway type)
- Hourly variations**, 32-35
 (see also Flow variations)
- Hourly volumes**
 design peak loads, 36
 normal peaking characteristics, 36
 one-way traffic, 27-28
 two-way traffic, 23-27
- Hourly volumes/AADT**, 36-42
- Ideal capacity**, 2
- Index of definitions**, 20-21
- Interchange connections**
 definition, 12
 effect on capacity, multilane rural highways, 289-291
- Intersection capacity**
 adjustment factors, 138-143
 buses, local transit, 142
 G/C ratio, 138
 trucks and through buses, 142
 turning movements, 138-142
 approach volumes, 133
 capacity charts and adjustment factors, 133-137
 G/C ratio, 133
 load factors, 137
 peak-hour factors, 133-137
 rural conditions, 136-138
 urban conditions, 133-137
 (see also Intersection capacity)
 interpretation, application of procedures, 143-155
 deficiency evaluation, 145
 signal split ratio, 146
 typical solutions, 146-155
 observed and computed values, 133
 vehicles per hour of green, 131
- Intersection capacity, service volumes**
 levels of service
 adjustment factor, 138-143
 capacity related to site factors, 129
 levels in terms of load factors, 131
 load factor as measure, 130-131
 Normann method of capacity determination, 112
 "point" level of service, 129-131
- Intersection operation**
 approaches
 capacity, 111, 129
 flow, 118
 urban volumes, 134
 volumes, 132
 bus factors, 143-145
 capacity, 111, 129
 estimation, 131
 factors affecting, 112
 four-way stop, capacity, 158
 general effect, 111
 "ideal," typical adjustments, 111
 interrupted flow and intersection operation, 111
 levels of service, 112, 129
 isolated, 131
 maximum volume, isolated, 131
 operational factors, 111
 rural, at two levels, 117
 service volume, 111, 129
 signalized intersections, 111
 capacity factors, 112
 unsignalized intersections, 155
- Intersections at grade**
 capacity, service volumes, and levels of service, signalized, 129-155

- estimation of capacity, service volumes and
 - levels of service, signalized
 - adjustment factors, 138-142
 - application of procedures, 143-146
 - capacity charts and tables, 133-137
 - factors affecting capacity, signalized
 - control measures, 126-128
 - environmental conditions, 115-121
 - physical and operating conditions, 112-114
 - traffic characteristics, 122-124
 - types defined, 12
 - unsignalized intersections, 155-159
 - applications of stop-sign control, 156
 - four-way stop sign control, 158
 - two-way stop sign control, 157
 - no control, 155
 - yield sign control, 156
- Junctions**
(See specific highway type)
- Land use and development**
definitions, 19
- Lane**
definitions, 10-12
- Lane distribution factors, 29**
- Lane markings**
definitions, 14
- effect on capacity, 128
- Lane operation**
effect of restricted width, 88-89
 - multilane, 285-286
- freeways and expressways, 255-256
- headways, 53
- number of lanes and effects, 129
- one-way streets, 129
- optimum number, 129
- speed by lanes, 46-47
- two-lane, effect of restrictions, 301, 303
- two-way, no parking, 129
- two-way, parking, 129
- width and capacity, 89
- Levels of service**
by type of facility, 80
- criteria, 79
- definition and discussion, 7-8, 78-87
- design speed, 79
- downtown streets, 333-334
- elements, 80
- evaluation, 80
- factors determining, 78
 - comfort, 78
 - convenience, 78
 - economy, 78
 - freedom to maneuver, 78
 - interruptions, restrictions, 78
 - safety, 78
 - speed and travel time, 78
 (see also specific roadway type)
- freeway and expressway, 245-252
- function of qualities, 22
- index to geometric combinations, 203
- interpretation, ramp analysis, 192-197
- levels of service A-F
 - at-grade intersections, 80-81
 - downtown streets, 332
 - freeways, 245-253
 - multilane rural highways, 283-284
 - operating conditions, 80-81
 - ramps, 191-197
 - three-lane highways, 317-318
 - two-lane highways, 300-303
 - urban and suburban arterials, 318-323
 - weaving, 173
- levels by volume, ramps, 192
- limits and ranges, 79
- multilane rural highways, 283-284, 296
- operating characteristics, 7
- operating speed as measurement, 191
- operating speed concept, 81
- quality of flow on weaving sections, 173
- travel speed, major factors, 78
- travel speed, operating speed, 79
- two-lane rural highways, 302
- urban and suburban arterials, 318-323
- v/c concept, 81
- v/c implications, 78
- v/c ratio, 78
(see also Intersection capacity, Ramps, Weaving sections)
- Load factors, 115-116**
as measure of level of service, 129-131
- definition, 17
- urban and suburban arterials, 321, 324
- Loading zones**
minimum length, 348
- Marking, lane**
(see Lane markings)
- Mass transit**
(see Buses)
- Maximum capacity**
ideal or possible, 2
(see also Levels of service)
- Maximum hourly volume, 23-28**
(see also Volume)
- Measure of effectiveness, 1**
- Merge and diverge**
criteria, ramps, 196, 226
- definition, 16
- significance, 191
- Multilane rural highways**
characteristics, 282
- computational procedures
 - basic subsections, 292, 294
 - capacity, one direction, 294
 - composite value for level of service, 296
 - equation for capacity, 294

- Multilane rural highways**
 computational procedures (*continued*)
 equation for service volume, 295
 level of service, 296
 point restrictions, 297
 service volume, one direction, 295
 "weighted" values capacity, volume, etc.,
 296-297
 critical elements
 access control and capacity, 291
 alinement, 291
 buses, 285-289, 290
 cloverleaf interchanges, 289
 cross connections, 291
 diamond interchanges, 291
 direct connection interchange, 289
 effect on capacity, diamond interchange,
 291
 grades, 285-289
 interruptions and interferences, 291
 lane width, 285, 286
 lateral clearance, 285-286
 railroad crossings, 291
 ramp connections, 289
 restrictions to flow, 285
 signalization, 291
 spacing of interruptions, effect, 292
 stop signs, 291
 strip development, 291
 trucks, 285-288, 290
 uninterrupted flow applicability, 292
 weaving areas, 286, 289
 examples, typical solutions, 298-299
 "ideal" conditions, 282
 levels of service
 Description, levels A-F, 283
 summary of relationships, 283-284
- Nomographs**
 extrapolation, ramps, 225
 lane-volume distribution at fork, 221
 ramp analysis, 204-221
- Normann method**
 capacity computations, intersection, 112
- One-way streets**
 (see Intersections at grade)
- Operating characteristics**
 (see specific roadway type)
- Operating conditions for level of service**
 six levels described, 80-81
- Operating speeds**
 (see specific roadway type)
- Parking**
 effect on intersection operations, 134-138,
 143-155
 effect on speed-flow, 67
 (see also specific roadway type)
- Passenger car equivalents**
 freeways, 257-261
 generalized, 301-306
 truck equivalent, 102
 (see also Equivalents)
- Passing sight-distance**
 (see Two-lane highways)
- Peak flows, 23-28**
 critical hours, 37
 design hourly volume, 37
 distribution of hourly volume, 37
 fifteen-minute rates, 34
 five-minute rates, 34
 frequency distribution, 36
 loading-unloading effects, 34, 36
 normal peaking characteristics, 36
 population density effects, 34, 36
 thirtieth (30th) highest hour, 38
 trends, 34
 trip generation relationships, 36
- Peak hour**
 determination, 37
 percent of AADT, 40
 public transportation at CBD, 338
 (see also Volumes)
- Peak-hour factor, 106, 117-119**
 definition, 17, 32-33, 117, 120
 signalized intersections, 133-137
 urban and suburban arterials, 321-327
- Peak period**
 expressways, 250
 peak period vs total peak-hour volume, 33
 (see also specific roadway types)
- Peak-period volumes**
 ramp analysis, 188
 volumes (buses), 340-342
- Poisson distribution**
 headways, 53-56
 hourly variations, 33
- Possible capacity**
 definitions, 2, 5
 discussion, 87
 (see also Levels of service)
- Practical capacity**
 definition, 2
 discussion, 87
 (see also Levels of service)
- Quality of flow, 173-176**
 (see also Weaving sections)
- Quality of service**
 capacity concept, 2
 (see also Levels of service)
- Queueing**
 headway distribution, 52-53
 wave movements, 72

Railroad crossings

effect on capacity, multilane rural highways, 291

Ramps

adverse effects of design inadequacies, 189
 calculation of service volumes A-C, 198-201
 calculation of service volumes D and E, 233-235

capacity near terminals, 196
 comparison of levels C and D, 244
 computational devices, levels A-C, 201-227
 computational procedures
 levels A-C, 198-225
 level D, 233-238
 level E, 242-244

computing junction requirements

adjustment factor for trucks, 224
 auxiliary lanes, 202, 222, 226
 calculating service volumes, general, 198, 250

equation substitutions, ramp, 225
 equations, nomographs, 201-221
 geometric combinations, 203
 lane-one volumes, 202-224
 left-hand ramps, 224
 merge and diverge criteria, 196-222
 nomograph extrapolations, ramp, 225
 nomographs, lane-one volumes, 204-221
 relating level of future service to design, 197-198

right-hand one-lane ramp, 224
 sampling, on site for ramp, 227
 simulation, digital computer, 227
 specialized application of procedures, 225-226
 specialized ramp design, 224
 specialized treatment, ramps, 225
 variables involved, 200

critical points, 197

definition, 12

effect on capacity, multilane rural highways, 289

effects on upstream volumes, 204, 396-397

examples, typical solutions

 levels A-C, 228-233
 level D, 239-242
 level E, 242-244

factors controlling capacity, 189-191

 entrance junctions, 190
 exit junctions, 191
 limiting factors, 189
 two-lane requirements, 190

influence of driver familiarity, 189

influence of geometrics, 188

junction analysis and performance, 187, 197

levels of service at terminals

 interpretation of, 192-197
 levels by volume, 192

 merging and diverging significance, 191

 operating speed as a measure, 191

 ramp terminal and freeway lane as a unit, 192

 peak-period volume, 188

 percent of through traffic, lane one, 235

 research reports, use of, 227

 volume analysis, 196, 204, 224, 236-238

 weaving between ramps, 188

Rate of flow

definition, 16

equation, 59

expressways, 249

maximum, 72

(see also Speed, flow, and density relationships)

References (chapter)

at grade intersections, 159

bus transit, 348

factors affecting capacity and service volume, 110

ramps, 244

weaving, 186

streets and highways without access control, 337

traffic characteristics, 73-74

Ribbon development, 262

Road types

definition, 8-10

(see also specific roadway types)

Roadway factors affecting capacity

adjustments, 108

alignment, 93-95

auxiliary lanes

 approach and exit expressways, 262-263

 bus lanes, 340-345

 climbing, 93, 100, 259

 computational procedures, 167, 202, 222

 expressways, 259

 parking lane effect, 91

 passing bays, 93, 101-102

 ramps, 202, 222

 refuge, 90

 reserved transit lanes, 340, 345

 speed change, 92

 storage and turn, 92-93, 111, 187

 truck climbing, 93

 weaving sections, 93, 160, 167, 187

grades

 approach to crawl speed, 97-99

 braking distance, 95

 climbing lanes, criteria, 100

 climbing performance, 95-99

 effects, 95

 general, 95-103

 passenger car equivalents, 100

 passing bays, 100, 102

 passing opportunities, 100

 sight distance, 95

 truck climbing, 106

 weight-power ratio, 98-99

Roadway factors affecting capacity (continued)

- lane width, 88-89
 - lane width and lateral clearance
 - freeway, uninterrupted flow, 256
 - multilane, uninterrupted flow, 256
 - two-lane, uninterrupted flow, 303
 - lateral clearance, 88-90, 255
 - affective restrictions, 89-90
 - effects of obstructions, 89
 - effect of trucks, 255-256
 - profile, 93-95
 - effect on capacity, 95
 - sight distance, 94
 - speed profile, 94
 - shoulders, 90
 - effect on capacity, 90-91
 - refuge for disabled vehicles, 90
 - surface condition, 93
 - widths
 - lane, 88
 - lane and clearance, 90
 - lateral clearance, 89
 - (see also Factors affecting capacity and service volume)
 - (see also specific roadway type)
- Rotaries**
- as related to weaving, 185-186
- Rules of the road, 156**
- Running time**
- definition, 16
- Rural intersections, 136-138**
- (see also Intersection operation)
- Rural volumes, maximum, observed, 23-26**
- Seasonal variations, 30**
- (see also Flow variations)
- Service levels**
- (see Levels of service)
- Service volumes**
- definition, 8
 - freeways and expressways, 295
 - multilane rural highways, 295
 - substitute for practical capacity, 2
 - two-lane highway, 309-313
 - (see also specific roadway type)
- Sight distance**
- definitions, 13
 - effect of restrictions, 301
- Signalized intersections**
- buses, local transit, effects of stops by type, 124-125, 346
 - components, geometry, traffic control, 112
 - control measures
 - marking approach lanes, 128
 - signal fundamentals, 126-128
 - signal timing, 127
 - signal types, 126
 - signal types, definitions, 14-15

environmental conditions

- area-wide population density, 120
 - balancing approach needs, 116
 - central business district, 121
 - fringe area, 121
 - jammed conditions, 116
 - land use, characteristics, 121
 - load factor, 112, 115-116
 - loaded phase, 115
 - locational approach capacities, 121-122
 - outlying business district, 121-122
 - peak-hour factor, 33, 117-119
 - peak-hour factor, determination of, 119
 - residential areas, 121
- factors affecting capacity, 112-129**
- Normann method, capacity determination, 112
- physical and operational, 113, 115**
- approach width, 113
 - one-way vs two-way operation, 114-115
 - parking control, 114
 - parking influence, 114
 - width utilization, 113
- predicted vs actual capacity, 112**
- research basis, 111-112**
- research needed, 112**
- left turns, 122
 - trucks and buses, adjustment factors for, 142
 - turning movements, 122-123
- Signals**
- effect on capacity, 127
 - effect on capacity, multilane rural highways, 291
 - effect on delay and speed, 66
- indications**
- green, flow rate, 126
 - lagging green, 141
 - leading green, 141
 - separate turn indications, 138-142
 - turn arrows, 138
- spacing on expressways, 263**
- timing, effect of, 127**
- Solutions, typical**
- (see Examples)
- Spacing and headway characteristics**
- definition, 16
 - density and measure
 - formulas, 58-59
 - speed, density, flow, as indicators, 59
 - headway distribution
 - by lanes, 53
 - composite exponential, 55
 - criteria for design, 56
 - free-flowing vehicles, 55
 - index of congestion, 56
 - platooning, 55
 - queueing, 52
 - random distribution, 53-56
 - restrained vehicle, 55
 - waiting time, 56-57

- interruption effects
 - desirability, 58
 - platooning, 56
 - recovery, 56-57
- mathematical relationships, 49
 - spacing and density, 51
 - spacing and headway relationships, 49
 - steady state relationships, 51
- measure of capacity
 - choice of speed, 51
 - effect on road user, 51
 - freedom of movement, 51
 - headway, minimum as constant, 52
 - speed, spacing relationships, 52
 - volume formulas, 51-52
- Speed characteristics
 - average, by vehicle type, 44
 - bus, on sustained grade, 104
 - daily variations
 - daytime-nighttime, 46
 - influencing factors, 46
 - speed/density/volume relationships, 45
 - definition by types, 15-16
 - distributions
 - constraint and effects, 47-48
 - day and night, 46
 - levels of service, 48-50
 - speed/volume relationships, 49-50
 - trends, 47-48
 - average overall travel speed, 319-323
 - effect of alinement, 95
 - levels of service, 62
 - mean, by lanes, 47
 - on signalized street, 67
 - operating speed
 - average, 44, 62
 - definition, 15
 - freeways and expressways, 247
 - measure of levels of service, 191
 - multilane highways, 283
 - ramps, 191
 - two-lane highways, 300-301
 - urban vs rural service, 44-45
 - passenger car distribution, 48
 - directional by lanes, 48
 - ideal, unidirectional, 49
 - multilane rural highways, 50
 - two-lane rural highways, 50
 - passenger car on expressways, 49
 - speed by lanes
 - influencing factors, 46
 - turbulence, effect of, 46
 - variation, 46-47
 - speed trends
 - desired speeds, 45
 - factors influencing speeds, 45
 - impact of capacity limitations, 45
 - measurement of average speed, 44-45
 - modern design, effect on, 45
(see also Daily speed variations)
 - through signalized street, 66
 - truck, related to grade, 97
 - variation
 - by time of day, 46
 - flow and speed, morning peak, 45
- Speed-density relationships
 - density and space mean speed, 68
 - interrupted flow, 70-71
 - similarity to uninterrupted flow, 70-71
 - speed-density, 70
 - uninterrupted flow, 67-69
 - critical vs maximum density, 68
 - normal, unstable, forced flow, 69
 - urban conditions, 71
- Speed, flow, and density relationships
 - ideal conditions, 60
 - predicting behavior, 60
 - simulations, 59
 - theoretical-empirical considerations, 60
- Speed-flow relationships
 - effect of parking, 67
 - interrupted flow, 65-67
 - arrival and discharge rates, 66
 - average delay, 66
 - average speeds, 66
 - break-points, 67
 - critical density, 67
 - influencing factors, 67
 - speed flow curves, 67
 - on three different highways, 61
 - uninterrupted flow, 60-65
 - average vs operating speed, 65
 - critical density, 60-62
 - curve characteristics, 61
 - factors affecting, 61
 - levels of service, 62
 - marginal friction, 61
 - operating speed, 62
 - space mean speed, 60
 - two-lane and multilane volumes, 63-65
- Speed, level of service, 49-50
- Speed, operating
 - related to v/c ratio, 264, 294, 310-312
- Speed trends
 - (see Speed characteristics)
- Speed, truck
 - change on grade, 100
 - on grade, 97
- Speed-volume relationships
 - at capacity, 300
 - discussion, 48-50
 - equation, 51
 - general diagram, 70
 - two-lane road, 50, 63-64, 299
 - weaving sections, 170-171

- Stop signs
 - applications, 156-157
 - effect on capacity, multilane rural highways, 291
 - four-way stop capacity, 158-159
 - two-way stop capacity, 157
- Streets and highways
 - characteristics, general, 280
 - evaluation, 281
 - factors controlling capacity, 281
 - levels of service, 280
 - limitations of applicability, 280
 - operating speed as determinant, 281
 - overall travel speed as determinant, 281
 - traffic characteristics, 281
 - variations, 280
 - v/c ratio as index of service, 281
 - v/c ratio related to speeds, 281
 - working v/c ratios, 281
 - definition, 8-9
 - downtown streets
 - breakdown conditions, 333
 - examples, solutions, 334-337
 - levels of service, 333-334
 - limitations to analysis, 332
 - multilane rural highways
 - computational procedures, 293-296
 - critical elements, 283-291
 - levels of service, 283
 - two-lane highways
 - computational procedures, 309-314
 - critical elements, 301-308
 - levels of service, 300
 - (see also specific roadway type)
- Terminals, ramp
 - definition, 13
 - levels of service, 191-197
- Thirtieth (30th) highest hour
 - design criterion, 43
 - forecasting, 44
 - relationship of AADT, 40-44
 - related to trip purpose, 43
 - (see also Design hour)
- Three-lane highways, 317-318
- Time variations
 - (see Flow variations)
- Traffic
 - definition, 15
- Traffic characteristics
 - effect on capacity, 122
 - general, 22-74
 - maximum observed volumes, 22-28
 - peak traffic, 25
 - range of capacities, 25
 - relationships of speed, flow, and density, 59-72
 - flow-density, 71-72
 - speed-density, 67-71
 - speed-flow, 60-67
 - spacing and headway, 49-59
 - density as measure of conditions, 58-59
 - effects of interruptions on, 56-58
 - headway, distribution and random flow, 52-56
 - mathematical relationships, 49-51
 - spacing as measure of capacity, 51-52
 - speed characteristics
 - average speed by lanes, 46-47
 - daily-speed variations, 45-46
 - speed distributions, 47-49
 - speed trends, 45-46
 - turning movements, 122-123
 - volume characteristics
 - hourly volume related to AADT and peak flows, 36-40
 - spatial variations, 25-29
 - time variations, 30-32
- Traffic control devices
 - definition, 14
 - (see also Intersection operations)
- Traffic factors
 - adjustments, 108-109
 - application, 108
 - summary, 109
 - at-grade intersections, 108
 - buses
 - adjustment factors, 105
 - bus speed capabilities, 104-105
 - equivalents, 257, 260, 287, 289, 304, 306
 - local transit, 105
 - passenger car equivalents, 105
 - flow variations, 106
 - critical areas, 106
 - effect of fluctuations, 106
 - peak-hour factor, 106
 - safety factor, 106
 - short-period flows, 106
 - interruptions, 106
 - lane distribution
 - critical area operation, 105
 - influence factors, 105
 - no special adjustment needed, 106
 - rate of flow, added lanes, 105
 - weaving, upgrades, 106
 - traffic interruptions and interferences, 291-293
 - at-grade intersections, 108, 111-159
 - effect on capacity, 308
 - effect on headways, 56
 - go rate from a stop, 107
 - other interruptions (toll-gates, RR crossings, etc.), 108, 326
 - reduced time utilization, 107
 - (see also specific highway type)
 - trucks, 101-102
 - adjustment factors, 102, 257, 261, 287, 290
 - definition, 15

- equivalents, expressways and freeways, 258
- equivalents, multilane highways, 288
- equivalents, two-lane highways, 101-102
- mixed traffic/passenger car equivalent, 102
- multilane adjustment, 102-103
- needed research in equivalents, 103
- passenger car equivalents, 103, 105
- Traffic flow
 - intersection approach, 118
 - variations
 - multilane rural, 358
 - multilane streets, 378
 - rural expressways, 356
 - rural freeways, 350
 - two-lane rural, 362
 - two-lane streets, 382
 - urban expressways, 376
 - urban freeways, 371
- Traffic operations
 - definitions, 15-19
- Travel desires
 - related to capacity, 2
 - related to seasonal fluctuations, 2
- Travel time
 - on signalized streets, 67
- Trucks
 - adjustment factors, 142
 - expressways, 257, 260
 - multilane, 290
 - two-lane, 304, 307
 - definition, 15
 - effect on capacity
 - intersections, 142
 - multilane rural highways, 285-290
 - equivalents
 - passenger car/truck, 258
 - passenger car/truck/bus, 287
 - passenger car/truck, multilane highways, 258, 288
 - passenger car/truck, two-lane highways, 304, 305
 - speed
 - change on grade, 100
 - on grade, 97
- Tunnels and bridges
 - (see Bridges and tunnels)
- Turn controls
 - adjustments factors, 140-141
 - (see also Signalized intersections)
- Turning movements
 - discussion, 122-123
 - effects on capacity, 122, 138-142
 - (see also Signalized intersections)
- Two-lane highways
 - access control, effect, 299
 - characteristics, 299
 - computational procedures (two-lane road)
 - basic subsection, 309-312
 - capacity, 309
 - equation, two-lane capacity, 309
 - equation, two-lane service volume, 313
 - level of service, 81, 314
 - service volumes, 309, 313
 - sight distance relations, 310-312
 - v/c ratio and operating speed, 309-312
 - critical elements
 - adjustment factors, 303
 - adjustment factors, equivalents, 306-307
 - alinement, 308
 - buses, 301
 - down-grade effect, 95-100, 306
 - frictions, 308
 - grades, 301
 - interference, 308
 - interruptions, 308
 - intersections, 111, 308
 - lane width, 301, 303
 - lateral clearance, 301, 303
 - passenger car equivalents, 301, 304-306
 - ramps, 111, 187, 308
 - trucks, 301
 - levels of service
 - operating characteristics, 302
 - restricted alinement, 301
 - restricted passing sight distance, 309
 - speed-volume at capacity, 300
 - volumes, effect on, 300
 - passing sight distance, influence, 299, 301
 - speed-volume relationships, 50, 63, 64, 299
- Two-way stop
 - intersection capacity, 157
- Two-way streets
 - intersection operations, 135
 - (see also Downtown streets)
- Uninterrupted flow
 - capacity, 76
 - effect of lane width, 89
 - effective width of roadway, 89
 - speed-flow relationships, 60
 - (see also Speed, flow and density relationships)
- Uninterrupted flow, ideal
 - factoring ideal to conditions, 109
 - summary of adjustments, 109
- Unsignalized intersections
 - capacities, 155
 - effect on traffic flow, 155
 - maximum capacity, 156
 - no control, 155-156
 - pro-rating signal split, 156
 - rules of the road, 156
 - stop sign control
 - applications, 156-157
 - four-way stop control, 158-159
 - two-way stop control, 157
 - yield sign control, 156

- Urban and suburban arterials
 - characteristics, 318
 - computational procedures, 327-329
 - capacity, 327
 - components, 327
 - levels of service, 328-329
 - overall analysis, 327
 - service volumes, 328
 - critical elements, 324-326
 - interference, 326
 - interruptions, 326
 - load factors, 324
 - one-way vs two-way operation, 325-326
 - progression criteria, 324
 - signalization, 111, 126, 263, 324
 - levels of service, 318-326
 - analysis, bases for, 321
 - capacity, 322
 - critical v/c ratio, 322
 - forced flow, 323
 - limitations in analysis, 319
 - load factors, 321, 324
 - overall analysis, 319
 - overall travel speed, 319
 - peak-hour factor, 321-322
 - point analysis, 318-319
 - range of volumes, 321
 - restraints to speed, 319
 - section limits, 321
 - typical relationships, 319-320
- Urban intersections
 - approach volumes, 134-136
 - (see also Intersection operations)
- Urban volume pattern
 - directional variations, 39
- Urban volumes
 - environmental effects, 39
 - flow rate, 78
 - peak traffic volumes, 39
- Urban volumes, maximum observed
 - one-way, by type of street, 27-28
 - two-way, by type of street, 23-27
- Variations in flow
 - (see Flow variations)
- Vehicles
 - definition, 15
- Vertical curves
 - types, effect, 97-98
- Volume
 - accumulated amount and percent, hourly re
 - annual volume, 37
 - approach at intersections, 118, 132-136
 - definitions, 8, 16, 19
 - distribution effects from ramps, 396-397
 - effects on land use, 30
 - effects on levels of service, 300
 - express buses, city streets and freeways, 341
 - express buses, various facilities, 342
 - fifteen-minute peak-hour factors, 34
 - fifteen-minute peak flow rate, 34
 - five minute re peak-hour flow, 35
 - frequency distribution, percent of difference,
 - estimated and observed flow rates, 36
 - highest reported, 23-28
 - hourly variations, 32
 - hourly variations, weekday, 32
 - hourly volumes related to highway type, 41-42
 - levels of service, uninterrupted, freeways and expressways, 252-253
 - maximum service
 - freeways and expressways, 252-253
 - multilane highways, 284
 - two-lane highways, 302
 - monthly variations, 31
 - peak-hour bus, 338-342
 - peak traffic, 25
 - peaking trends, 34
 - percent of ADT for various hours, 38-39
 - rank order, hourly volumes for year, 37
 - rate of flow, estimated vs observed, 36
 - related to levels of service, 22
 - service, 2
 - traffic demand, 22
 - urban vs rural, 29
 - variation by time of day, 46
 - variation, flow and speed, morning peak, 45
 - weekly variations, 31
 - (see also Speed, flow and density relationships, and Hourly volumes, Speed characteristics)
- Volume/capacity (v/c) ratio
 - determination of service level, 246
 - operating speed, expressways, 264
 - operating speed, multilane highways, 294
 - operating speed, two-lane highways, 310-312
 - overall travel speed, 320
- Volume-capacity relationships
 - discussion, 76
 - expressways, 247-251
- Volume characteristics
 - hourly re AADT and peak flow, 36
 - hourly re AADT, 39
 - peak-hour determination, 37
 - spatial variations, distribution, 25-29
 - traffic compositions, 29
 - trends in highest hour, 40
 - variations, seasonal, 30-34
- Volume measurements
 - AADT, 37
 - AADT in surfaced mileage groups, 29
 - demand synthesis, 37
- Volume-speed relationships
 - expressways, 62
 - freeways, 66
 - multilane rural highways, 63
 - two-lane rural highways, 63

- Volumes, maximum observed
 one-way, 27-28
 two-way, 23-27
- Weaving sections
 between ramps, 188
 capacities, selected observations, 386, 388
 capacity and levels of service, 173-176
 definition, 13
 design and operational evaluation, 176-186
 factors affecting capacity, 160, 286-289
 formation, 161
 formulas for design, 168-169
 length requirements and determination, 167
 levels of service, 173
 maximum volume, 170
 operating characteristics, 164-172
 added lanes for outer flow, 167
 classes of traffic, 165
 factors involved, 165
 non-weaving movements, outer flow, 165
 weaving movements, 165
 quality of flow, 166-167, 170, 173
 quality-volume, relationships, 170-171
 simple arrangements, 163
 speed-weaving volume-length relationships,
 170-172
 types of weaving sections, 162-164
 urban areas, 185
 width requirements, 168
- Weekly volume variations, 32
- Weighted level of service
 for composite value expressways, 268-270
- Width of roadway, effective, 89
 in lanes, 10
- Yellow interval, 138
- Yield sign control
 capacity, 156