

estimates in the more detailed and exact terms (the probability of property damage, injury or fatality) needed to compare appurtenance or safety improvement alternatives on a cost/benefit basis.

5. The relationship between occupant safety and vehicle dynamics during interaction with a highway appurtenance is very tenuous because it involves to many widely varying factors such as occupant physiology, size, seating position, attitude and restraint and vehicle interior geometry and padding. For this reason, it appears that a "general" tie could best be developed between vehicle compartment acceleration and the probability of occupant injury. This tie should probably be based on unrestrained occupants unless the use of restraint systems becomes mandatory in the future. The development of such a tie would enable researchers to go back to make new injury severity judgments for past vehicle/appurtenance crash tests where good acceleration data were documented.

6. It is reasonable for the minimum acceptable occupant injury levels to vary, dependent on the type of highway safety appurtenance involved. This is on the basis that the "art of the possible" enables lower impact resistances to be achieved, for example, with small highway signs compared with crash cushions.

7. Efforts are underway by others, such as under NHTSA sponsorship, to develop an improved instrumented anthropomorphic dummy that would be more capable of simulating human movements and recording human injury indicators in the occupant compartment during a vehicle/appurtenance crash test. The development of an improved dummy would enable researchers to make more detailed and accurate injury severity predictions. The dummies currently used in vehicle/appurtenance crash tests do not provide this capability.

8. Efforts have been made in the past by researchers such as Michalski in Oregon and Olson in Texas to relate the degree of injury sustained in an accident to the vehicle damage. Although considerable additional work would be necessary, it may be possible to relate the observed type and magnitude of vehicle damage to occupant compartment accelerations, which in turn could be related to occupant-injury severity.

9. A better tie between crash test data and "real-world" accident injury severity could also be developed by reconstructing actual accidents where vehicle/appurtenance variables such as occupant restraint, vehicle damage, impact speed, impact angle, etc., and the actual level of injury are known. Known accidents could be reconstructed in controlled crash tests and simulated in computer programs. Through this process, the relationship could be developed between the data currently acquired in a vehicle/appurtenance crash test and the severity of injury that occurs in real-world accidents where the parameters are similar to vehicle/appurtenance crash tests already performed. This would reduce the cost of such an effort.

ISSUE: UTILIZATION OF SIMULATION TO PREDICT  
LIKELIHOOD OF INJURY

William T. Hollowell, National Highway Traffic Safety  
Administration, Moderator

Other group members: Richard L. Chiapetta, Keith  
Friedman, David J. Segal, Lawrence F. Spaine

The discussions first centered about the role simu-

lation has in the benefit evaluation for a proposed countermeasure to be introduced to the highway roadside. In considering all the parameters associated with the accident environment, it was concluded that crash testing alone provided limited data for a full benefit evaluation, and therefore simulation could fill the data needs provided that a meaningful analysis could be accomplished. The essential ingredients of a meaningful analysis included: an accurate depiction of the accident environment, an accurate (qualitatively and more desirably quantitatively) vehicle-roadside object simulation, an accurate occupant model and an accurate injury predictor model (based on deterministic occupant responses). The discussion then was directed toward each of the simulations.

The vehicle-roadside object simulations were first discussed. In particular, the status of the GUARD, CRUNCH, BARRIER VII and HVOSM models was presented with a particular emphasis placed on the data needs of the models for simulating the accident environment. Such data as soil-post interactions were mentioned to be lacking. A special concern expressed was the validation of simulation output compared with crash test results and/or accident reconstructions. Also, the changing fleet of automobiles presents a benefit evaluation problem in that an accurate projection of fleet distribution and characteristics are required for the evaluation effort.

The occupant models were discussed. It was generally agreed that, for the accidents simulated, a three-dimensional occupant simulator was required. In particular, the Calspan 3-D Crash Victim Simulator (CVS) was discussed. The particular data needs for this model included accurate data for modeling various size occupants, accurate geometry of the compartment interior, accurate energy absorbing characteristics of the vehicle interior components, accurate crash pulses from the vehicle-roadside object simulations, accurate models of the restraint systems, etc. Of prime importance was the need to make the CVS model user friendly. In that detailed data sets are required for the model, it was determined that efficient handling of data sets would lead to fewer man-hours required by the engineer to construct the model for the analysis.

The discussion next centered on the prediction of injury and hence leading to the prediction of the likelihood (or probability) of injury as related to physical information. First, the transformation of results processed from crash test data to injuries observed in the accident environment is required. Second, responses calculated from occupant models are generally different from those obtained from crash testing. Hence, a transformation from occupant simulation is required to close the loop compared with the injuries observed in the accident environment. Ongoing research being conducted by Chi Associates (probability of injury) and the University of Virginia /Safety Systems Optimization Model (SSOM)/ was discussed as to how these goals are being approached.

The concluding discussion then centered on performing the benefit evaluation once the models are in place. Again, the SSOM was discussed as to how that model approaches the evaluation. In addition, the Benefits Prediction Model (BPM) was discussed.